

Mathematical Analysis of Pulse Tube Cryocoolers Technology

Amit medhavi¹, Ravi Prakash Vishvakarma² and Dr. Shashank Kumar Kushwaha³

¹ K.N.I.T Sultanpur

Received: 10 February 2012 Accepted: 2 March 2012 Published: 15 March 2012

Abstract

The cryocoolers are being developed for use in space and in terrestrial applications where combinations of long lifetime, high efficiency, compactness, low mass, low vibration, flexible interfacing, load variability, and reliability are essential. Pulse tube cryocoolers are now being used or considered for use in cooling infrared detectors for many space applications. In the development of these systems, as presented in this paper, first the system is analyzed theoretically. Based on the conservation of mass, the equation of motion, the conservation of energy, and the equation of state of a real gas a general model of the pulse tube refrigerator is made. The use of the harmonic approximation simplifies the differential equations of the model, as the time dependency can be solved explicitly and separately from the other dependencies. The model applies only to systems in the steady state. Time dependent effects, such as the cool down, are not described. From the relations the system performance is analyzed. And also we are describing pulse tube refrigeration mathematical models. There are three mathematical order models: first is analyzed enthalpy flow model and heat pumping flow model, second is analyzed adiabatic and isothermal model and third is flow chart of the computer program for numerical simulation. These mathematical reviews describe cryocoolers working and operation.

Index terms— cryocooler, various applications, different types of cryocooler and mathematical analysis.

1 Introduction

ryogenics comes from the Greek word "kryos", which means very cold or freezing and "genes" means to produce. A Cryocooler is closed cycle cooler of a device which is used to cool inside the environment of anything and increasing need in cryogenic temperature in research and high conductivity during the last decade caused a rapid development of cryocoolers. In a country like India [1],

The cost of liquid Helium and liquid Hydrogen is increasing, cryocoolers can play a very important role [1]. Its Refrigeration powers vary from about (0.15 W to 1.75 w). The ability of the device to cool its interior environment depends largely on the thermodynamic properties of the gas circulating through the system. Cryocooler may be classified into different types of pulse tube which called various name, the important factors are discussed that have brought the pulse tube refrigerator to its current position as one of the most promising cryocoolers for a wide variety of applications [2].

2 II.

3 Applications

The main requirement is it's cooled below 120k which is use in various applications, area is very large. Cryocoolers are refrigerating machines, which are able to achieve and to maintain cryogenic temperatures [3]. The recuperative coolers use only recuperative heat exchangers and operate with a steady flow of refrigerant through the system. The compressor operates with a fixed inlet pressure and a fixed outlet pressure. If the compressor is a reciprocating

type, it must have inlet and outlet valves (valve compressor) to provide the steady flow. Scroll, screw or centrifugal compressors do not need valves to provide the steady flow [4]. Figure 2 shows schematics of the most common recuperative cryocooler cycles. Expansion of the liquid in the JT capillary, orifice, or valve is relatively efficient and provides enough of a temperature drop that little or no heat exchange with the returning cold, expanded gas is required. Thus, a very efficient recuperative heat exchanger is required to reach cryogenic temperatures.

4 Classification of Cryocooler

5 i. Joule Thomson Cryocoolers ii. Brayton Cryocoolers

In Brayton cryocoolers (sometimes referred to as the reverse Brayton cycle to distinguish it from a heat engine) cooling occurs as the expanding gas does work. Figure shows a reciprocating expansion engine for this purpose, but an expansion turbine supported on gas bearings is more commonly used to give high reliability. According to the First Law of Thermodynamics the heat absorbed with an ideal gas in the Brayton cycle is equal to the work produced.

The Brayton cycle is commonly used in large liquefaction plants. For small Brayton cryocoolers the challenge is fabricating miniature turbo expanders that maintain high expansion efficiency. The expansion engine provides for good efficiency over a wide temperature range, although not as high as some Stirling and pulse tube cryocoolers at temperatures above about 50 K. The low-pressure operation of the miniature Brayton systems requires relatively large and expensive heat exchangers [7]. In regenerative types the refrigerant undergoes an oscillating flow or an Oscillating pressure analogous to an AC electrical system. The compressor and the pressure Oscillator for the regenerative cycles need no inlet or outlet valves. The regenerator has only one flow channel, and the heat is stored for a half cycle in the regenerator matrix, which must have a high heat capacity. The performance of the regenerative type cryocoolers is dependent on the phase difference between the pressure and mass flow rate phases. Helium is the refrigerant of choice for most regenerative type cryocoolers [8].

6 2012

May gas in the proper phase relationship with the pressure oscillation. When the displacer is moved downward, the helium gas is displaced to the warm end of the system through the regenerator. The piston in the compressor then compresses the gas, and the heat of compression is removed by heat exchange with the ambient.

The Joule-Thomson cryocoolers produce cooling when the high pressure gas expands through a flow impedance (orifice, valve, capillary, porous plug), often referred to as a JT valve. The expansion occurs with no heat input or production of work, thus, the process occurs at a constant enthalpy. The heat input occurs after the expansion and is used to warm up the cold gas or to evaporate any liquid formed in the expansion process [5]. The main advantage of JT cryocoolers is the fact that there are no moving parts at the cold end. The cold end can be miniaturized and provide a very rapid cool down. This rapid cool down (a few seconds to reach 77 K) has made them the cooler of choice for cooling infrared sensors used in missile guidance systems. These coolers utilize a small cylinder pressurized to about 45 MPa with nitrogen or argon as the source of high pressure gas. Miniature finned tubing is used for the heat exchanger. An explosive valve is used to start the flow of gas from the high pressure bottle. The higher boiling point components must remain a liquid at the lowest temperature [6].

Next the displacer is moved up to displace the gas through the regenerator to the cold end of the system. The piston then expands the gas, now located at the cold end, and the cooled gas absorbs heat from the system it is cooling before the displacer forces the gas back to the warm end through the regenerator.

In an ideal system, with isothermal compression and expansion and a perfect regenerator, the process is reversible. Thus, the coefficient of performance COP for the ideal Stirling refrigerator is the same as the Carnot COP given by (1) Where the net refrigeration power is, is the power input, T_c is the cold temperature, and T_h is the hot temperature. The occurrence of T_c in the denominator arises from the PV power (proportional to T_c) recovered by the expansion process and used to help with the compression. Practical cryocoolers have COP values that range from about 1 to 25% of the Carnot value.

Stirling cycle consists of four thermodynamic processes acting on the working fluid: Points 1 to 2, Isothermal Expansion. Points 2 to 3, Constant Volume (known as isovolumetric or isochoric) heat removal. Isothermal Compression (Point 3 to 4), Points 4 to 1, Constant Volume (known as iso-volumetric or isochoric) heat addition [9]. 2. The piston moves down to compress the gas (Helium) in the pulse tube. It flows through the orifice into the reservoir and exchanges heat with the ambient through the heat exchanger at the warm end of the pulse tube. The flow stops when the pressure in the pulse tube is reduced to the average pressure. 3. The piston moves up and expands the gas adiabatically in the pulse tube. 4. This cold, low pressure gas in the pulse tube is forced toward the cold end by the gas flow from the reservoir into the pulse tube through the orifice. As the cold gas flows through the heat exchanger at the cold end of the pulse tube it picks up heat from the object being cooled. The flow stops when the pressure in the pulse tube increases to the average pressure. 5. The cycle then repeats. The displacer is eliminated. The proper gas motion in phase with the pressure is achieved by the use of an orifice and a reservoir volume to store the gas during a half cycle. The reservoir volume is large enough that negligible pressure oscillation occurs in it during the oscillating flow. The oscillating flow through the orifice separates the heating and cooling effects just as the displacer does for the Stirling and Gifford McMahon refrigerators. The orifice pulse tube refrigerator (OPTR) operates ideally with adiabatic compression and expansion in the pulse

102 tube [10]. In the pulse tube refrigerator the cooling actually occur in the oscillating pressure environment. The
103 heat is absorbed and rejected at the two heat exchangers. It is a cyclic process.

104 Because PTR operates in steady periodic mode, the thermodynamic properties such as enthalpy flow , heat flow
105 and power are evaluated in the form of cyclic integrals. The appropriate instantaneous thermodynamic properties
106 are integrated over the entire cycle and divided by the period of that cycle to obtain the cyclic averaged quantity
107 of interest [11]. For example, the compressor power is evaluated from the following integration.

108 $\int_0^{\tau} P dV$

109 Where f is frequency is period of the cycle, P and V , are instantaneous pressure and volume respectively. The
110 average enthalpy flow over one cycle and average heat flow rate are also calculated similarly.

111 $\int_0^{\tau} \dot{Q} dt$

112 7 Ptr Efficiency

113 In an ideal PTR the only loss is the irreversible expansion through the orifice. The irreversible entropy generation
114 there is a result of lost work that otherwise could have been recovered and used to help with the compression
115 [12]. All other components are assumed to be perfect, and the working fluid is assumed to be an ideal gas. The
116 COP for this ideal PTR is given by VI.

117 8 Component Development a) Expander

118 The expander assembly is the key cooling system component, enabling the actualization of a cryocooler with high
119 efficiency, compact size, and low mass. The expander is a transducer that operates by creating an electrostatic
120 force between two electrodes in a precision capacitor and allowing pressurized gas to separate the electrodes. The
121 gas does work against the electrostatic force by separating the electrodes. This work is eventually dissipated as
122 Joule heating in a warm load resistor. By doing work and removing it from the system, the expansion process
123 can be carried out at nearly isentropic state and the dissipated energy provides an efficient means to reduce the
124 gas temperature.

125 The expander is configured in an opposing piston arrangement and as gas is expanded on one side, the already
126 cooled gas is expelled on the opposite side. In figure one side of the expander is being filled by opening a series
127 of valves to the high pressure side of the system, figure the gas is expanded in the left side while the previously
128 expanded and cooled gas on the right side is expelled to the low pressure side of the system. $\eta = \frac{W}{Q} = \frac{P \Delta V}{Q} = \frac{P \Delta V}{P \Delta V + P \Delta V} = \frac{1}{2}$

129 wear mechanisms by balancing the forces and resultant moment on the orbiting scroll while allowing the fixed
130 Scroll to translate radially and axially, thereby minimizing contact forces between surfaces. Balance is achieved
131 by configuring two orbiting scrolls mounted from a common base plate and mechanically driving the base plate
132 from the outer edge or from a rigid central hub. Using this method, the forces can be reacted about the base
133 plate producing no net off axis torque that can contribute to seal or wear.

134 To balance the axial forces that act on the scroll tips, an external gas pressurization scheme is employed. A
135 pressurized gas volume is maintained external from the compression space on the backside of the fixed scroll
136 to apply an axial force. The force on the fixed scroll will then just slightly exceed the separation force acting
137 between the orbiting and fixed scrolls from the compressed gas. This applies a well controlled, Cryocooler uses
138 a series of heat exchangers to achieve its thermodynamic efficiency, these include an after cooler to reject the
139 heat generated in the compression process, recuperative counter flow heat exchanger between the high and low
140 pressure gas streams, and cold end heat exchanger to interface with the element that are cooled. Effective heat
141 exchange in each of the exchangers is paramount to achieving high system efficiency, but recuperate presents the
142 largest challenge in terms of realizing a compact design that has high net effectiveness [13]. $\eta = \frac{Q_c}{Q_h} = \frac{Q_c}{Q_c + W} = \frac{1}{1 + \frac{W}{Q_c}}$

144 9 d) Regenerator

145 The regenerator is the most important component in pulse tube refrigerator. Its function is to absorb the heat
146 from the incoming gas during the forward stroke, and deliver that heat back to the gas during the return stroke.
147 Ideally, PTC regenerators with no pressure drop and a heat exchanger effectiveness of 100% are desired, in order
148 to achieve the maximum enthalpy flow in the pulse tube. The performances of the real regenerators are of course
149 far from ideal. Stainless steel wire screens are usually selected as the regenerator packing material, since they
150 offer higher heat transfer areas, low pressure drop, high heat capacity, and low thermal conductivity.

151 10 e) Rotary Valve

152 It is used to switch high and low pressure from a helium compressor to the pulse tube system. The high and low
153 pressure of helium compressor are connected to the rotary valve through the quick disconnect couplings. The
154 rotary valve has a Rulon part which is made to rotate with the help of a synchronous motor against an aluminum
155 block with predefined passages connecting the high and low pressures from the helium compressor [14]. The
156 rotational frequency of the synchronous motor is controlled using an inverter drive.

157 The rotary valve has been designed to produce pressure wave in the frequency range from 1Hz to 3Hz. A
158 typical design of rotary valve is shown in Fig 10. Suppose that in the beginning of the cycle the gas parcel at
159 position X 1 has temperature T_1 and the temperature distribution of the wall is given as line 1-2. Consider the

160 first half cycle where the pressure increases from the lowest to the highest. During this period, the gas parcel flows
 161 towards the closed end of the pulse tube to position X 2 undergoing an adiabatic process, hence its temperature
 162 increases to T_3 . Since $T_3 > T_2$, therefore heat is rejected to the wall by the gas parcel until temperature of the
 163 gas parcel equals to that of the wall T_2 . During the next half cycle, this gas parcel flows backward. This is an
 164 adiabatic expansion process where the temperature of the gas parcel decreases to T_4 . Since $T_4 < T_1$, the gas
 165 parcel has refrigeration effect at the position X 1. This is so called surface heat pumping theory [15]. Where
 166 the period of the cycle is, C_p is the heat capacity.

167 The pharos quantities and are mass flow rate and temperature respectively.). Mass flow rate shown in right
 168 to right hand place shown in figure 14), On the other hand, if an oscillating mass flow rate is out of phase with
 169 oscillating gas temperature T , then little or no enthalpy flow will exist in the pulse tube, which results in minimum
 170 cooling. Figure, depicts two examples of phase shift between gas temperature and mass flux.

171 The first example in Fig. 13 demonstrates a case where the mass flow rate and the temperature oscillations
 172 are about 90 degrees apart. In this circumstance, little or no enthalpy flow takes place. In fact, with temperature
 173 and the time mass flow rate being 90 degrees out of phase, one phase quantity will always be zero when the
 174 other one is at its peak. Thus, out of phase relationships tend to produce poor refrigeration due to minimum
 175 enthalpy flow in the pulse tube. On the other hand, if the mass flow rate and the temperature oscillations
 176 are in phase as illustrated in the second example (Fig. 14), good enthalpy flow can exist in the pulse tube.
 177 Thus in phase and out of phase are the two extreme conditions. In actual pulse tube there are exists same phase
 178 difference between the phase quantities [17]. The working process of the pulse tube refrigeration system is very
 179 complex due to the unsteady, oscillating compressible gas flow, the porous media in regenerator, the presence
 180 of the orificereservoir, the double inlet valve etc. The cooling effect at cold end of the pulse tube occurs due to
 181 compression and expansion of the gas column lies somewhere between the adiabatic and isothermal processes,
 182 and may be assumed to be a polytrophic process. To understand the basic phenomenon responsible for the m
 183 production of cold effect at the pulse tube section, two limiting cases adiabatic and isothermal processes involving
 184 ideal gas have been considered. Both these models are approximate models which are dealt separately.

185 The following assumption has been made with adiabatic behavior of the gas. The regenerator, the cold end and
 186 hot end heat exchangers have been assumed to be perfect. That means that the regenerator will always maintain
 187 a constant temperature gradient between its hot and cold ends at steady operation [18]. And heat addition at
 188 cold end heat exchanger and heat rejection at hot end heat exchanger of pulse tube occur at constant temperature
 189 at steady conditions. The pressure wave in the pulse tube is provided with a compressor directly coupled to the
 190 hot end of the regenerator. This design is more compact and more efficient than the valve compressor with gas
 191 distributor design [19]. The compressor cylinder has been assumed to be adiabatic in the analysis, since each of
 192 the compression and expansion processes occurs in such a short period of time that little heat exchange between
 193 the gas and the cylinder wall can be affected. The gas adiabatically compressed in the cylinder is assumed to be
 194 cooled to room temperature by the adjacent after cooler. The after cooler has been assumed to be perfect, so
 195 that the temperature of the gas leaving it is always equal to its wall temperature.

196 **11 iii. Change in Compressor Volume**

197 Sinusoidal variation has been taken for the compressor cylinder volume variation. (7) Where V_0 = clearance
 198 volume, V_S = stroke volume and f = frequency Applying the first law of thermodynamics to the control volume
 199 drawn around the volume swept by the piston in the cylinder and Compressor pressure variation is expressed as
 200 (8) Fig. 16 : control volume cylinder iv. Pressure Variation at the Pulse Tube Pulse pressure variation is a
 201 function of compressor pressure variation. So the pressure variation in the pulse tube can be derived in terms of
 202 compressor pressure variation along with various mass flow rate involved in the system. The cold end mass flow
 203 rate equation derived earlier is (9) Where T_C and T_H are the temperatures at cold end and hot end respectively
 204 and R is a gas constant. In case of double inlet pulse tube refrigerator, the mass flow rate through the double
 205 inlet valve (DI) is due to the pressure difference between compressor and pulse tubes [20] $P_P P_P a t x t x ? ?$
 206 $? ? ? ? + ? + = ? ? ? ? 2 , p a ? ? ? = = 0 () [1 \sin(2 \theta)] 2 S c p V V t V f t = + + ? [] c p c p c p c p d p$
 207 $d V m c R T P d t d t = ? ? t t H c h C c V d p T m m T R T d t ? = + d i m d h x V c m r g m d r g d c x t t r g c c r g$
 208 $V V d P d P m m R T d t R T d t = + + +$

209 The cold end mass flow rate is given as,
 210 $() 0 1 h t t c d i d h x C c T V d P m m m V T R T d t ? = ? + +$
 211 Compressor out let mass flow rate is given as:

212 v. Pressure Variation at the Reservoir Pressure variation at the reservoir is due to the mass flow through the
 213 orifice and it is given as: (13) vi. Mass Flow through Regenerator Mass flow in the regenerator has been evaluated
 214 through Argon's equation, (14) Where the porosity of the porous medium is, ρ is the density of the fluid, d_h the
 215 hydraulic diameter, μ is the dynamic viscosity of the fluid and A_{rg} is the cross section area of the regenerator.
 216 Assuming d_{Lrg} (length of regenerator) and d_p ($P_{cp} P_t$)

217 vii. Mass Flow through Orifice Mass flow through the orifice has been assumed as a nozzle flow, calculated
 218 from well known formula for a nozzle with a correction factor [21]. (15) Where $P_t P_r$ (16) Where $P_t P_r$ viii.
 219 Mass Flow Rate through Double Inlet Valve Mass flow rate through double inlet valve has also been assumed
 220 as nozzle flow similar to that in the orifice. Here the mass flow occurs due to pressure differences between
 221 compressor and the pulse tube. Therefore, mass flow rate has been calculated as (17) Where $P_{cp} P_t$ (18)

222 Where $P_{cp} P_{td}$) Second Order of Isothermal Model Analysis In this model, the compression and expansion
 223 processes are considered as isothermal. It shows higher efficiency than the adiabatic or any other model of
 224 the pulse tube. For the purpose of analysis, a pulse tube refrigerator system is divided into a few subsystems,
 225 which are coupled to each other. Different researchers have used different schemes for dividing the full pulse
 226 tube refrigerator into subsystems. The pulse tube device has been divided into six open subsystems. Three of
 227 them exchange work, heat and mass with the surroundings (compressor, cold and hot volumes), while the others
 228 exchange mass only (regenerator, double inlet valve and orifice reservoir). It has been assumed that all heat
 229 exchanges are at constant temperature and that temperature of all subsystems exchanging heat is equal to those
 230 of the heat reservoirs. Another condition is that mechanical equilibrium is realized in each part of the device.
 231 These conditions lead to the model presented in Figure 17. The system described in the figure consists of six
 232 opened subsystems as (In the figure point 1 is compressor, 2 is after cooling, 3 is regenerator, 4 is cold end, 5 is
 233 hot end, 6 DI valve, 7 is orifice and 8 is reservoir) [22], [23].) i. Governing Equations
 234 $\frac{dp}{dt} = \frac{R}{V} \frac{dV}{dt} + \frac{R}{V} V \frac{dT}{dt}$
 235 $\frac{dp}{dt} = \frac{R}{V} \frac{dV}{dt} + \frac{R}{V} V \frac{dT}{dt}$ (1)

236 Figure 18 shows a control volume which represents an isothermal variable volume. iii. For Pulse Tube Similarly
 237 to that in compressor, the pulse tube flow has been assumed to be a piston like flow. In other words, the displacer
 238 of the Stirling or the GM cryocooler has been converted into a gas piston. The pulse tube has been divided into
 239 two distinct volumes, one for cold volume V_c and the other for the hot volume V_h at uniform temperature to
 240 ensure the reversibility of the model [26], [27]. (22) iv. For Cold Volume (23) v. For Hot Volume (24) (25) The
 241 pressure variation in the pulse tube is the addition of two pressure variations in cold and hot volume.

242 12 ()

243 dv

244 13 Conclusion

245 In this study, first part is basic study of different types of cryocooler. Result is pulse tube type cryocooler is
 246 more reliable, no vibration etc. Second part, PTR efficiency method, flow properties, characteristic analysis and
 247 mathematical analysis use to find PTR different kind of equation to help for simulation techniques and various
 248 type of software such that fluent, CFD, and MATLAB etc. Mathematical analysis also use to find improved
 249 design and modification, it has now become the most efficient cryocooler for a given size. It is suitable for a wide
 variety of application from civilian to government to military and from ground equipment to space systems.



Figure 1: a. Military 1 .



Figure 2: Fig 1 :

250
251

1 2

¹F © 2012 Global Journals Inc. (US)

²© 2012 Global Journals Inc. (US)



Figure 3: Fig. 2 :



Figure 4:



3

Figure 5: Fig. 3 :

cryocooler

54

Figure 6: Fig. 5 :Fig. 4 :

recuperative

6

Figure 7: Fig. 6 :

Regenerative

87

Figure 8: Fig . 8 :Fig. 7 :

With

9

Figure 9: Fig. 9 :

valve

10

Figure 10: Fig. 10 :

Valve

11

Figure 11: Fig. 11 :

less

13

Figure 12: Fig . 13 :

Gifford Mc

14

Figure 13: Fig. 14 :

115

Figure 14: 1 .Fig. 15 :

Mahon

6

Figure 15: (6)

Stirling vuilleumier

Figure 16:

brayton

17

Figure 17: Fig. 17 :

Joule

18

Figure 18: Fig. 18 :

thomson

Figure 19:

claupe

19

Figure 20: Fig. 19 :



[Note: c Q]

Figure 21:

- 252 [Walker and Cryocoolers] , Graham Walker , Stirling Cryocoolers . *Cryocoolers Part-1* p. .
253 [Cryogenics ()] , *Cryogenics* 2001. p. .
- 254 [Radebaugh et al. ()] ‘A comparison of three types of pulse tube refrigerators: New methods for reaching 60 K’.
255 R Radebaugh , J Zimmerman , D R Smith , B Louie . *Adv. in Cryogenic Engineering* 1986. Plenum Press.
256 31 p. 779.
- 257 [Berchowitz et al. (1977)] ‘A New Mathematical Model for Stirling Cycle Machine’. D M Berchowitz , C J Rallis
258 , I Urieli . *Proc.* (nullWashington, D.C.) 1977. August 28-September 2. p. . (12 th I.E.C.E.C.)
- 259 [Baek et al. (2000)] Sang Baek , Ho , Eun Jeong , Soo , Sangkwon Jeon . *Twodimensional model for tapered*
260 *pulse tubes. Part 1: theoretical modeling and net enthalpy flow*, 2000. 40 p. .
- 261 [Marquardt and Radebaugh ()] ‘Compact High Effectiveness Parallel Plate Heat Exchangers’. E D Marquardt ,
262 R Radebaugh . *Cryocoolers* 2003. Kluwer Academic/Plenum Publishers. 12 p. .
- 263 [De Waele and Hooijkaas ()] A T A M De Waele , H W G Hooijkaas . *Flowcontrolling devices in pulse tubes”;*
264 *accepted for proceedings CEC/ICMC-99*, (Montreal) 1999.
- 265 [Radebaugh ()] ‘Development of the pulse tube refrigerator as an efficient and reliable cryocooler’. R Radebaugh
266 . *Proc. Institute of Refrigeration*, (Institute of RefrigerationLondon) 1999-2000. (in press)
- 267 [Shaowei et al. ()] *Double inlet pulse tube refrigerators: an important improvement*, Zhu Shaowei , Wu Peiyi ,
268 Chen Zhongqi . 1990. p. .
- 269 [Duband et al. (ed.) ()] L Duband , I Charles , A Ravex , L Miquel , C Jewell . *Experimental results on inertance*
270 *and permanent flow in pulse tube coolers”;* *Cryocoolers*, R G RossJr (ed.) (New York) 1999. 10 p. . (Kluwer
271 Academic / Plenum publishers)
- 272 [Shaowei and Zhongqi ()] ‘Enthalpy flow rate of a pulse tube in pulse tube refrigerator’. Zhu Shaowei , Chen
273 Zhongqi . *Cryogenics* 1998. 38 p. .
- 274 [Cai et al. ()] ‘Experimental analysis of the multi bypass principle in pulse tube refrigerators’. J H Cai , J J Wang
275 , W X Zhu , Y Zhou . *Cryogenics* 1994. 34.
- 276 [Ni (2003)] ‘Floating Scroll Technology for Fuel Cell Air Management System’. S Ni . *Fuel Cell Technology* April,
277 2003.
- 278 [Zhu and Chen ()] *Isothermal model of pulse tube refrigerator*, S W Zhu , Z Q Chen . 1994. 34 p. .
- 279 [Mikulin et al. ()] ‘Low temperature expansion pulse tubes’. E I Mikulin , A A Tarasov , M P Shkrebyonock .
280 *Adv. in Cryogenic Engineering* 1984. Plenum Press. 29 p. .
- 281 [Wu and Zhu ()] ‘Mechanism and numerical analysis of orifice pulse tube refrigerator with a valve less compres-
282 sor’. P Wu , S Zhu . *Proc. Int. Conf., Cryogenics and Refrigeration*, (Int. Conf., Cryogenics and Refrigeration)
283 1989. p. .
- 284 [Dunmire ()] ‘Military and commercial applications for low cost cryocoolers’. H Dunmire . *Electronic Industries*
285 *Association (EIA)* Jan. ’98. 1998. (Army cryocooler status update)
- 286 [Wu et al. ()] ‘Numerical modeling of orifice pulse tube refrigerator by using the method of characteristics’. P Y
287 Wu , Li Zhang , L L Qian , L Zhang . *Advances in cryogenic engineering* 1994. 39 p. .
- 288 [Smith] *One-dimensional models for heat and mass transfer in pulse-tube refrigerators*, W R Smith .
- 289 [Boyle et al. ()] ‘Overview of NASA Space Cryocooler Programs’. R F Boyle , R G Ross , Jr . *Advances in*
290 *Cryogenic Engineering 46B*, S Breon (ed.) (New York) 2002. AIP. p. .
- 291 [Performance study on a twostage 4 K pulse tube cooler Adv. in Cryogenic Engineering ()] ‘Performance study
292 on a twostage 4 K pulse tube cooler’. *Adv. in Cryogenic Engineering* 1997. 1998. Plenum Press. 37 p. .
293 (Cryogenics)
- 294 [Gifford and Longs Worth ()] *Pulse tube refrigeration*, W E Gifford , R C Longs Worth . 1964. Trans ASME B
295 J Eng Industry. 86 p. .
- 296 [Gifford and Longs Worth ()] ‘Pulse tube refrigeration progress’. W E Gifford , R C Longs Worth . *Advances in*
297 *cryogenic engineering* 1964. 3 p. .
- 298 [Nellis et al. ()] ‘Reverse Brayton cryocooler for NICMOS’. G Nellis , F Dolan , J McCormick , W Swift , H Six
299 Smith , J Gibbon , S Castles . *Cryocoolers* 1999. Plenum Press. 10 p. .
- 300 [Roy et al. ()] *Some theoretical and Experimental Studies on Pulse tube refrigeration*, P C Roy , S K Sarangi , P
301 K Das . 2003. Dept. of Mech. Engg. IIT Kharagpur (MS Thesis)
- 302 [Gifford and Longs Worth ()] ‘Surface heat pumping’. W E Gifford , R C Longs Worth . *Advances in cryogenic*
303 *engineering* 1966. 11 p. .
- 304 [De Boer ()] *Thermodynamic analysis of the basic pulsetube refrigerator*, P C T De Boer . 1994. 34 p. .
- 305 [Wang et al.] C Wang , G Thummes , C Heiden . *A two-stage pulse tube cooler operating below 4 K*,