



GLOBAL JOURNAL OF RESEARCHES IN ENGINEERING: E
CIVIL AND STRUCTURAL ENGINEERING
Volume 22 Issue 1 Version 1.0 Year 2022
Type: Double Blind Peer Reviewed International Research Journal
Publisher: Global Journals
Online ISSN: 2249-4596 & Print ISSN: 0975-5861

Methodology and Evaluation of Large Deformations in Romanesque Pillars

By Josep Lluís I Ginovart, Cinta Lluís-Teruel & Mónica López-Piquer

Universitat Internacional de Catalunya

Abstract- There is a set of Romanesque churches at Val d'Aran that were built between the eleventh and thirteenth centuries. One of the main features of these buildings is the presence of large deformations masonry as in the church of Santa Maria d'Arties (XII) in which arches and vaults have funicular shapes. The assessment is based on a three-dimensional model obtained with a terrestrial laser scanner (TLS). Geometrical evaluation of the least rigid elements, the pillars, allows to analyze the displacements. It is not only possible to deduce the regression plane of the central-nave pillars' displacements but also to define the deformation vectors over it. The methodology of this study focuses on the assessment of the deformations they have suffered. The point cloud is processed with the software Cyclone, the program 3DReshaper (2016) and, finally, with Google SketchUp (2019).

Keywords: *romanesque, barrel vaults, masonry pillars, great deformations, val d'aran.*

GJRE-E Classification: *DDC Code: 823.914 LCC Code: PR6056.O45*



Strictly as per the compliance and regulations of:



© 2022. Josep Lluís I Ginovart, Cinta Lluís-Teruel & Mónica López-Piquer. This research/review article is distributed under the terms of the Attribution-NonCommercial-NoDerivatives 4.0 International (CC BY-NC-ND 4.0). You must give appropriate credit to authors and reference this article if parts of the article are reproduced in any manner. Applicable licensing terms are at <https://creativecommons.org/licenses/by-nc-nd/4.0/>.

Methodology and Evaluation of Large Deformations in Romanesque Pillars

Josep Lluís I Ginovart ^α, Cinta Lluís-Teruel ^σ & Mónica López-Piquer ^ρ

Abstract- There is a set of Romanesque churches at Val d'Aran that were built between the eleventh and thirteenth centuries. One of the main features of these buildings is the presence of large deformations masonry as in the church of Santa Maria d'Arties (XII) in which arches and vaults have funicular shapes. The assessment is based on a three-dimensional model obtained with a terrestrial laser scanner (TLS). Geometrical evaluation of the least rigid elements, the pillars, allows to analyze the displacements. It is not only possible to deduce the regression plane of the central-nave pillars' displacements but also to define the deformation vectors over it. The methodology of this study focuses on the assessment of the deformations they have suffered. The point cloud is processed with the software Cyclone, the program 3DReshaper (2016) and, finally, with Google SketchUp (2019).

Keywords: *romanesque, barrel vaults, masonry pillars, great deformations, val d'aran.*

I. INTRODUCTION

The churches of Val d'Aran are located at the Spanish Pyrenees and were built between the twelfth and thirteenth centuries. Large deformations have been found on these Romanesque buildings masonry and are one of the main characteristics of them. In the church of Santa Maria de Arties (XII-XIII), the most deformed building, some antifunicular shapes have been found at their arches and vaults (Lluís i Ginovart, et alli, 2021: 210-221). This funicular shape is the inverse of the natural shape of an arch since it is convex in relation to its centerline. The case-study of this paper focuses on the church of Santa Maria d'Arties, which is the most assessed building of the group. Its great deformations were identified during the restoration works of the 70's (Saez, 1976). Afterwards, José Luis i Villanueva noted the existence of funicular shapes (Villanueva, 1974) and, in 2009, the structure was studied by means of finite elements method (FEM) by the team of Joan Polo i Berroy (Polo, 2009).

The deformation presents a typical pattern leaning vertical elements towards the outside because of vaults thrust and settlement, which is the cause of the apparition of funicular shapes. One of the apparition of

funicular shapes. One of the reasons of these deformations in Santa Eularia d'Unha, Santa Maria d'Arties and Era Purificacio de Bossost is the displacement of the pillars since they are the least rigid elements of the structure (figure 1).

The study of the deformation of the walls and the pillars was done through the transversal sections where the deformations parallel to the plane was analyzed. For this, it was necessary to measure the vertical deformation of walls and columns, as a vault and wall must work jointly to transmit the weight. The investigation focuses on the geometrical parametrization and on the evaluation of these movements. Previous investigations set the assessment of the overall structure to understand the stability conditions, revealing that masonry was working to its limit, with the maximum status of deformation, and this plus the displacements had their origin in the rigidity of the structure.

The assessment was based on a three-dimensional model obtained with a terrestrial laser scanner (TLS). Direct measurement techniques for architectural heritage surveying requires many resources and the use of massive data capture by terrestrial laser scanner (TLS) has recently become prominent. On the other hand, topographic documentation of the heritage is a keytool for its preservation. Current techniques of massive data capture (MDC), such as digital photogrammetry and terrestrial laser scanner, have become widespread and numerous investigations have tested their reliability proving their effectiveness to survey the building's geometry with high precision. Point clouds make it possible to detect and track degradation processes and formal anomalies. Other applications go from heritage documentation to delve in the history of buildings constructions (Dhonju,"et alli", 2017). The specific issue of deformation assessment is essential for architectural heritage conservation. Many studies have developed simple procedures to address the issue from the 3D topographical information of the point clouds, e.g., the Cathedral of St. Johannis in Meldorf (Sternberg, 2012), the Cathedral of Tortosa (Lluís i Ginovart, "et alli", 2016; 42-50), the churches of Santa Maria in Portonovo (Quagliarini "et alli", 2016).

Author α: *Dean of School of Architecture Barcelona, Universitat Internacional de Catalunya. e-mail: jlluis@uic.es*

Author σ: *Associate professor and PhD Candidate at Universitat Internacional de Catalunya. e-mail: cintalluis@uic.es*

Author ρ: *PhD Candidate at Universitat Internacional de Catalunya. e-mail: mlopezp@uic.es*



Fig. 1: Deformation of the pillars: Santa Eularia d'Unha, Santa Maria d'Arties and Era Purificacio de Bossost

To analyze the deformations of the church of Santa Maria d'Arties (XII-XIII), we used the point cloud extract from the scanner Leica ScanStation P20, with a bandwidth of 808/658, class 1. The point cloud was processed with the software Cyclone and the program 3DReshaper version 2016, used to obtain the three-

dimensional mesh with an average distance of points of 0.05 m as well as a measure of the triangle for detecting 0.1m holes. The model of the interior of the building has 80.582 points and 156.449 triangles, and the exterior has 314.650 points and 609.472 triangles (figure2a).




Fig. 2: Visualization of Santa María's pillars: a) Software Cyclone; b) Software Undet

The point cloud has been processed with the plugin Undet, of the software Google SketchUp version 2019. Nevertheless, in this occasion, the point cloud was not converted to a mesh because this plugin works with points, not with meshes. The models have a grid of

points in coordinates (x, y, z) ranging from 0,06 to 0,09 m. (figure 2.b).

II. METHODOLOGY OF THE GEOMETRICAL ASSESSMENT OF PILLARS

The methodology of this study focuses on the assessment of the geometrical characteristics of the six pillars [P1...P6] of Santa Maria d'Artes with the objective of studying the displacements that they have suffered (figure 3). The pillars of the central nave have deformed in a specific way, namely, through the masonry joints (ns). These joints are perfectly visible on pillars P3, P4, P5 and P6, while they are more difficult to visualize on P1 and P2 since they are partially covered by mural paintings. The displacement of a particle in Cartesian coordinates (x, y, z) with its corresponding orthonormal base ($\hat{e}_1, \hat{e}_2, \hat{e}_3$) starts from a reference configuration Ω_0 , where the position vector (X) of a particle G (corresponding to the center of gravity) in space is defined by the material coordinates; $X = X_1 \hat{e}_1$

+ $X_2 \hat{e}_2 + X_3 \hat{e}_3 = X_i \hat{e}_i$; (x1, x2, x3). When moving to the current configuration Ω_t , occupying spatial point G', the position vector (x) in spatial coordinates at a snapshot of time (t) will be given by $X' = X'_1 \hat{e}_1 + X'_2 \hat{e}_2 + X'_3 \hat{e}_3 = X'_i \hat{e}_i$; (x1, x2, x3). This change in position is represented by a displacement vector, $u_G = (u_{Gx}, u_{Gy}, u_{Gz})$ (figure 4).

The displacements can be assessed according to the coordinates of the centroid of each row (xci, yci, zci), and the point of reference is taken from the row of the floor plan, which is believed that it is nondeformable. This establishes the coordinates as (xci, yci, 0). These points allow defining a regression plane Pr1 for each pillar. Thus, it is possible to define a vector of deformation contained on each plane [Pr1...Pr6]. Finally, this data allows to determine the general tendency of vaults' deformations (figure 5).



Fig. 3: Geometrical characteristics of the 6 pillars [P1...P6] of Santa Maria d'Artes




Fig. 4: Displacement of the center of gravity in the section of the pillar P3 of Santa Maria d'Artes



Fig. 5: Above is the example of single column image. Images must be of very high quality

The assessment of shapes can only be understood in three dimensions through an interval (a, b) which must impose the condition of equilibrium according to the elastic theory and the summation of the active thrusts (E_{ba}) of the vaults and the passive thrusts of the walls (E_{mp}) and buttresses (E_{mc}) [1].

$$\sum_h^a F(x,y,z)(E_{ba} + E_{mp} + E_{mc}) = 0$$

$$\sum_h^a M(x,y,z)(E_{ba} + E_{mp} + E_{mc}) = 0. \quad [1]$$

The forces caused by the vaults are transmitted to the vertical structural elements. The vaults of the central nave are supported by the walls over former arches which, at the same time, are supported by the pillars of the central nave. Thus, the elements can

deform over the three planes, the pillars dfp ($dfpx$, $dfpy$, $dfpz$), and the perimeter walls dfm ($dfmx$, $dfmy$, $dfmz$). On the other hand, the deformations of the pillars are a function of their monolithic nature. Therefore, the deformations are directly related to the stone cutting of the pillar and the thrust Ep (Epx , Epy , Epz). According to the internal distribution of forces, the masonry stone cutting, the mortar ($Epz1$) and the irregular geometry of the vault ($Epz2$), the structure tends towards a state of equilibrium ($Epz1 - Epz2$) or to the opposite state ($Epz1 + Epz2$).

A monolithic, infinitely rigid pillar tends to rotate on its base. The upper part moves over the axis (x) towards the exterior, since the main horizontal thrust (Ex), with the consequence that there is also movement in the axis (y) since their extreme upper part declines. Finally, there is also movement over axis (z), due to Ebz , which defines the deformations dfp ($dfpx$, $dfpy$, $dfpz$).




Fig. 6: Representation of displacements on the regression planes P_{ri} over (y)

Pillars are not monolithic and are built with numerous joints, they tend to deform in the upper part so that there is no Δ dfpy. If we suppose that the extremes of the vaults have not suffered differential settlements and that the movement of these extremes is, thus, ($\Delta z=0$), then the deformations are dfp (dfpx, 0, dfpz) which is the hypothesis of the present case study. There can be a combination of rotations and translations, as a function of the stone cutting, so the general characterization of the displacements should be made through intervals I1; dfp (dfpx, dfpy, dfpz). Then, in I2, dfp (dfpx, 0, dfpz) displacements ($\Delta y > 0$) can occur because of the contact between mortar and stones or due to the friction between stones where there is no more mortar. The displacement of the pillar can be deduced through analysis of the displacement of the centroid of n sections (ns) of the pillar. Thus,

coordinates (xci, yci, zci) are set for each section (ns). The centroid of reference (xc0, yc0, zc0) is set in the section of the floor plan since it would have not suffered any displacement (figure 6).

The reparation and containment of these deformations are the cause of the reinforcement of the perimeter walls by means of the construction of buttresses or strategical placement of bell towers, which are usually built in the opposite façade to the apse. The active thrusts (Eba) of the vaults over pillars and walls have been determined, but to understand the equilibrium of these constructions, it is essential to understand the passive thrusts of the buttressing elements, walls (Emp) and buttresses (Emc). Due to these thrusts, some vaults have deformed towards funicular shapes (figure 7).



Fig. 6: Passive thrusts of the buttressing elements, walls (Emp) and buttresses (Emc)

III. DATA TREATMENT WITH THE SOFTWARE CYCLONE

The use of the specific software Cyclone to process the data enables to visualize the obtained point-cloud and to process and join all the scanners done to convert the point-clouds to a mesh. This processing occurs through an automatic process with slight manual adjustments, so a complete-depurated point cloud and a triangular mesh are obtained.

The morphological features assessment of the pillars is made through the visible elements, such as the masonry joints. Non-visible elements are not considered. Thus, data is obtained according to the centroids of each visible row. Thus, pillars have following

rows: (P1 =26), (P2=26), (P3= 27), (P4= 25), (P5= 23) and (P6= 23). Rows are numbered from bottom to top the identification of pillars' joints was made by means of a manual measurement system because the graphical capacity of the software Cyclone and the program 3DResheaper do not allow to specify pillar's joints because it constructs them three-dimensionally (Lluis I Ginovart, "et alli", 2017).

The greatest displacement is found in pillar P1, with a range of displacement on each row of [0.270, 0.001]. This displacement is followed by that in pillar P3, with a range of [0.190 – 0.001]. The range of displacements of the rest of the pillars is as follows: P2 [0.108 – 0.002], P4 [0.109 – 0.002], P5 [0.101 – 0.001], and, finally, the least deformed pillar, P6 [0.065 – 0.001].

Thus, pillars P1, P3 and P5 have greater deformations than the others. None of the regression planes P_{ri} is perpendicular to the axis of the central vault. Each one is moderately sloped. The angle in P1 is 85.466° , so $(\omega \phi) < 90^\circ$. It is also the most inclined pillar (0.270 m) and is

the highest (4.170 m). The rest of the pillars have angles $(\omega \phi) > 90^\circ$ with a range $[103.893^\circ - 126.169^\circ]$; [P2; 103.893°], [P3; 108.665°], [P4; 117.245°], [P5; 112.066°] and [P6; 126.169°] (figure 8).




Fig. 8: Characterization of the regression planes P_{ri} from Cyclone (2016)

IV. DATA TREATMENT WITH THE PLUGIN UNDET FOR GOOGLE SKETCHUP

Using the plugin Undet for Google SketchUp 2019, the identification of pillar's joints was made directly with the image of the software. Undet is a plugin that combines individual scan stations into groups and point-clouds from a wide range of scanners. In this case, we have used the data extracted from the Massive Data Capture (MDC) of the Leica ScanStation P20 scanner. What we have experienced with this plugin is that the management of the point-clouds is more efficient and quicker than with the software Cyclone.

Undet for SketchUp 2019 has interactive coloring and density management so it let us to adjust transparency, change point-cloud and points size and, the most important thing for our research, we can see the point cloud colored by planes or heights. This function lets us see pillar's joints in detail so, from now on, we will be able to check the manual measurement previously done and to express that the joints measured with Undet range from 0.007 m to 0.015 m of width. We have also analyzed the regression planes P_{ri} from the pillars, which, like the previous results obtained from the software Cyclone, are also non-perpendicular to the axis of the central vault.

We observed that there are little differences between the other results and these ones, being the

deformation of P2 the biggest difference (2.599° less) and the one of P3 the smallest (0.003° less). The angle in P1 is 85.474° , so $(\omega \phi) < 90^\circ$, and it is also the most inclined pillar (0.206 m). The rest of the pillars have angles $(\omega \phi) > 90^\circ$, as we have previously seen, with a range $[101.291^\circ - 124.756^\circ]$: [P2; 103.893°], [P3; 108.657°], [P4; 119.417°], [P5; 124.756°] and [P6; 110.553°] (figure 9).

We have also seen that the deformations of P4 and P5 are bigger in the middle of pillars height than at the top of it. With Cyclone we did not find those deformations. The obtained results from both methods used are very similar to determine deformations in Romanesque masonry buildings, where the interest of the displacements is more qualitative than a quantitative order of magnitude. The graphic precision of the plugin Undet for Google SketchUp 2019 should be noticed, since it is higher and, therefore, allows the identification of the masonry joints of the pillars that each point composing the point-cloud extracts from the Terrestrial Laser Scanner (TLS). To work with this plugin, there is no need to have a computer with a lot of graphic capacity, and the point-cloud can be sectioned in few seconds. Regarding to its precision, in a section of 0.005 m, the error is about 0.006 m (0.030%), unlike the one obtained from the software Cyclone (2016), which was 0.03m.

Otherwise, the vectorization of the displacements of each row, deduced from the regression plane, makes it possible to parametrize the leaning of each pillar. In addition, two deformation modes were identified, so the displacements of the

pillars are not uniform. Moreover, on pillars (P2, P3, P5), the displacements are variable and appear to be negative displacements on (y) in relation to the vertical, and the deformation of pillars (P1, P5, P6) is biggest in the middle of their height than in their extremes.




Fig. 9: Characterization of the regression planes P_{ri} from the plugin Undet

V. CONCLUSIONS

The obtained regression planes P_{ri} , which contain the deformations d_{fp} (d_{fpx} , d_{fpy} , d_{fpz}) for each pillar, tend to have the direction of the thrust over the pillar P_i . These displacements are the result of the active thrusts of vaults $[(E)_{ba}]$ and the passive thrusts of the buttressing system, walls $[(E)_{mp}]$ and buttresses $(E)_{mc}$. This study revealed that the direction of the displacements of the six pillars P_i is not perpendicular to the central axis of the church ϕ_1 , since $(\omega\phi) \neq 90^\circ$. This result proves the hypothesis that the thrusts of the vaults are not perpendicular to the axis of the church, as was the case of Roman vaults, which Choisy (1873) [27] defined with regular geometry and stone cutting. The direction of displacements is caused by the irregular geometry of the vaults of Santa Maria d'Arties as well as the masonry stone cutting and the above-mentioned passive thrusts of the walls and buttresses. The last ones were placed to maintain equilibrium during the last millennium (figure 10).

The displacement of the five pillars ($P_2 \dots P_5$), where $(\omega\phi) > 90^\circ$, tends to the opposite façade of the apse. In addition, pillars P_5 and P_6 , built during the twelfth century on that façade, are the least deformed pillars because of two subsequent transformations: the construction of the bell tower over the center of the façade (XIII-XIV) and the wood choir (XVIII). These elements have a stiffening function. Pillar P_1 is the most

deformed of Santa Maria d'Arties and has $(\omega\phi) < 90^\circ$ over the main axis. The displacement tends to the apse. This pillar, together with pillar P_3 , where $(\omega\phi) > 90^\circ$, have achieved a great balancing through the passive thrust of the walls (E_{mp}) and buttresses (E_{mc}). For a specific weight of more than 24 kN/m³, the buttressing system weights 3144,96 kN. It is here where funicular shapes and inverted arches have appeared, therefore: $f''(x) > 0$. Pillars deformations d_{fp} (d_{fpx} , d_{fpy} , d_{fpz}) tend to have the same direction of the thrust over pillars P_i , so regression planes P_{ri} , which contain these deformations, are essential to define any intervention over these masonry buildings because they show the direction for possible preventive actions. The ranges of heights where great deformations occur have also been identified and are: P_1 ; [1.50 – 2.00 m], P_2 ; [3.00 – 3.50 m], P_3 ; [2.00 – 3.00 m], P_4 ; [1.50 – 2.50 m], P_5 ; [2.00 – 3.00 m] and P_6 ; [1.00 – 2.50 m]. There is a difference between the height of the base pillars too due to the inclination of the church floor, being P_1 and P_2 of the same height from their base center, and P_3 of the same height of P_4 , but beginning 0.047 m upper than P_1 and P_2 , and, finally, P_5 is 0.0577 m upper than P_1 and 0.019 lower than P_6 . These points are extremely important to determine the appropriate actions that need to be taken for intervention on these buildings to preserve the Romanesque architectural heritage.




Fig. 10: Vectorization of the displacements of each row from the regression plane

REFERENCES RÉFÉRENCES REFERENCIAS

- Dhonju, H., Xiao, W., Shakya, B., Mills, J., & Sarhosis, V. (2017). Documentation of Heritage Structures Through Geo-Crowdsourcing and Web-Mapping. ISPRS Geospatial Week, pp. 17-21.
- Lluis i Ginovart, J., Costa-Jover, A., Coll-Pla S., & Puçe Fontanilles, J. M. (2016). Techniques of massive data capture: A comparative approach for the assessment of complex spaces in architectural heritage. *Revista de la Construcción*, 15, 1, pp. 42–50.
- Lluis i Ginovart, J. Coll-Pla, S., Costa-Jover, A., López-Piquer, M. (2017). Evaluation of large deformations on Romanesque masonry pillars; The case of Santa Maria d'Arties. *Revista de la Construcción*, 16, 3, pp. 468-478, <http://dx.doi.org/10.7764/rdlc.16.3.468>.
- Lluis i Ginovart, J., Lluis-Teruel, C., Coll-Pla, S., Costa- Jover, A. (2021) Large deformations in barrel vaults: from anti-funicular to funicular vaults. *Revista Ingeniería de la Construcción*, 36, 2, pp: 2010-2021. <http://dx.doi.org/10.4067/S07180732021000200210>.
- Polo, C. (2009). Santa Maria d'Arties (Naut Aran, Val d'Aran); Un exemple integrat a nivell de restauracion d'un monument a compdar des entresenhe arqueologiques. *Cicle de Conferències Patrimoni Arqueològic I Arquitectònic a Les Terres de Lleida 2009*, Departament de Cultura I Mitjans de Comunicació. pp. 75-103.
- Quagliarini, E., Clini, P., & Ripanti, M. (2017). Fast, low cost and safe methodology for the assessment of the state of conservation of historical buildings from 3D laser scanning: The case study of Santa Maria in Portonovo (Italy). *Journal of Cultural Heritage*, 23, pp.175-183. <https://doi.org/10.1016/j.culher.2016.10.006>.
- Saez, G. (1976). Primera fase del proyecto de restauración de la Iglesia de Santa María de Arties en el Valle de Arán (Lérida). *Cuadernos de Arquitectura y Urbanismo*, 116, pp. 63-71.
- Sternberg, H. (2012). Deformation measurements at historical buildings with terrestrial laser scanners. *IAPRS, Volume XXXVI, Part 5, Dresden 25-27 September*. pp. 303–308.
- Villanueva, J. L. (1974). "Las bóvedas de cañón.". *De Re Restauratoria*, Vol. II, 145–158). Barcelona: UPB.