

# Characterization of Fuel Properties for the Biodiesel-Petro-Diesel Blends Dosed with the FPC

Molelekoa James Mosesane<sup>1</sup>, Mbayana R. K.<sup>2</sup>, Tshabalala L.C<sup>3</sup> and Kalombo L<sup>4</sup>

<sup>1</sup> Tshwane University of Technology

*Received: 3 February 2015 Accepted: 3 March 2015 Published: 15 March 2015*

---

## Abstract

The effect of the Fuel Performance Catalyst (FPC) on the different diesel properties namely density, viscosity and flashpoint of biofuel has been investigated. The biodiesel-petro-diesel blends concentrations (Vol

---

*Index terms*— FPC, biodiesel, petro-diesel, biodiesel-petro-diesel blend, viscosity, density, flash point.

## 1 Introduction

Due to the fluctuating cost of common petroleum products (petro-diesels) and the need to reduce fuel consumption worldwide, there has been a renewed investment in the development of the alternative energy sector in South Africa (White Paper, 2006). According to Pradhan and Mbohwa (2014), South Africa is the largest energy consumer amongst the African countries as it contributes to about 31% of Africa's primary energy consumption. The highest energy demands have been predominantly attributed to the transport sector. In light of this, the Department of Minerals and Energy (DME) initiated the development of a Bio-fuels Industrial Strategy in the year of 2005, to systematically quench these growing energy demands (White Paper, 2006). Later, the Position Paper was published in terms of National Energy Act 34 of 2008. However, challenges such as biodiversity, impacts on food security, lack of understanding of the new technology and slow agricultural development due to land use changes have stalled the targeted biofuel commercialization potential over the years (Avinash A. et al, 2014 (Mobida E. et al, 2014).

Nevertheless, studies have been conducted in recent years to investigate the economic viability of biodiesels derived from vegetable or animal fats as well as synthetic diesels from biomass, biogas, natural gas, and coal (Avinash A. et al, 2014 (Mobida E. et al, 2014). A detailed account on the production of biodiesel can be found elsewhere (Mittelbach M. and Gangl S., 2001; Kivevele T. and Huan. Z., 2015). The effects of different formulations of biodiesel and petro-diesel blends on fuel flow properties such as density and viscosity have been investigated by numerous scholars (Mittelbach M. and Gangl S. 2001; Kivevele T. and Huan. Z., 2015, Enmeremadu C.C., 2011). All these studies aided in developing a knowledge base on the potential alternative fuel sources and the effects of blending different fuels in order to create a better fuel economy.

In addition, successful reports on studies aiming on the reduction of fuel consumption in South African UD60 diesel trucks using a homogenous catalyst called the Fuel Performance Catalyst (FPC) have been reported by Mosesane et al (2015). Elsewhere, scholars such as Zhang (2009) also reported positive results on the performance of this catalyst. The FPC is a homogenous diesel additive made from ferrous picrate with a complex concoction of short-chain alkyl benzenes ( $\pm 87\%$ ), n-butanol ( $\pm 12\%$ ), dioctyladipate ( $\pm 1\%$ ) and a common plasticizer (Zhang, 2009). Although the fuel consumption studies have been documented, there is still a knowledge gap on the effects of the FPC on the stability of the density and viscosity of pure petro-diesels, biodiesels and their blends. Characterization of these properties is crucial as they determine the ease of flow and atomization in diesel engines (Schwab A.W. et al., 1987).

Numerous researchers have investigated different biodiesel-petro-diesel blends on various diesel engines to examine fuel performance characteristics such as exhaust emission parameters (Durbin, T. D. et al, 1999), energy output, thermal efficiency and other fuel performance associated properties (Nwafor, O.M.I. and Rice, G., 1996; Misra, R.D. and Murthy, M.S., 2011). Their formulations showed comparable performance in relation to the

46 pure diesel. Their results also showed a reduction in harmful exhaust gas emissions by the biodiesel-petro-diesel  
47 blends as compared to the pure diesel feeds. Common blends may range from a ratio(s) of 2:98% (B2) up to  
48 100% (B100) by volume. Although biodiesels are miscible with petro-diesel in a variety of proportions, not all  
49 formulations may be used in diesel engines as an increase in biodiesel concentration increases both fuel density  
50 and viscosity (Enmeremadu C.C., 2011). According to the Engine Manufacturers Association (EMA), blends of  
51 up to 20% biodiesel and 80% petro-diesel (B20) can be used in nearly all diesel equipment and are compatible  
52 with most storage and distribution equipment. Blending ratios higher than B20 may clog up the engine piping  
53 systems and also necessitate engine modifications (Schwab A.W. et al., 1987). Hence, the warranty on most new  
54 engines only allows a maximum of B 20 to be used as reported by Enmeremadu (2011). Biodiesel blends of up to  
55 20% have been reported to reduce emissions of hydrocarbon (HC), carbon monoxide (CO), sulphur dioxide (SO  
56 2 ), and particulates as well improve the engine performance (Balat and Balat, 2008; ??hang et al, 2003).

57 In this regard, this work aims at studying the effect of the FPC on the flow properties namely; density and  
58 viscosity of biodiesel-petro-diesel mixtures of different ratios. Flash point tests have also been incorporated to  
59 the test matrix to account for the minimum temperature at which the fuel burns when subjected to an external  
60 heat source. This work forms part of the biodiesel-petro-diesel blending investigations in terms of Act 120 of  
61 1997 in line with the position taken by the South African petroleum regulators (White paper, 2006 and Green  
62 Cape, 2013).

## 63 2 II.

### 64 3 Materials and Methods

65 The biodiesel used was produced by Matayo Bio-fuels Pty Ltd, South Africa using the Fuel Meister 2 which  
66 requires vegetable oil with about 0% to 10% Free Fatty Acid (FFA) content. Samples of biodiesel and petro-diesel  
67 (50ppm Sulphur) were collected from the Matayo storage tank and the local Garankuwa filling station respectively.  
68 The experiments were carried out in two stages namely: (i) FPC and Biodiesel-Petro-diesel blending and (ii)  
69 Fuel blend property characterization involving density, viscosity and flash point investigations. All measurements  
70 were carried out in at least three repetitions. For each set of conditions, the mean was used for analysis.

### 71 4 a) Fuel blending

72 The fuel blends formulated in this work are made up of a volume by volume (Vol %) mixture of biodiesel and  
73 petro-diesel at ratios of 10:90, 20:80 and 30:70 to expand the test range. These were given acronyms of B10,  
74 B20 and B30 respectively. The FPC dosed batch of the B10, B20 and B30 blends was added to the experiment  
75 matrix at an FPC: Biodieselpetro-diesel ratio of 1:10 000 by volume. FPC dosages were made using a Gilson  
76 micropipette. All blending was performed at room temperature. All doses of biodiesel or FPC were added to the  
77 petro-diesel under continuous mixing by a magnetic stirrer in a 500mL beaker.

### 78 5 b) Fuel density and viscosity determination

79 The fuel density was analyzed as a function of temperature using a Rudolph Research Analyzer -Automatic  
80 Density Meter in accordance with ASTM D1250 standard. Viscosity was measured using a Brookfield DV II +  
81 Pro Viscometer as per ASTM D7467-13 standard. All samples were subjected to a temperature range of 20-80°C  
82 with 5°C increments.

### 83 6 c) Fuel flashpoint determination

84 The fuel flashpoint investigations were conducted using a Normalab Flashpoint Tester which was set at 60°C as  
85 per NFEN 22719 standards. Samples of 75mL were poured into a flash point cup which was connected to the  
86 regulator bath to steadily increase the sample temperature from 20°C to a maximum of 80°C.

## 87 7 III.

### 88 8 Results and Discussion

#### 89 9 a) Fuel blending

90 In the Fig. ?? are shown the density data obtained for the pure biodiesel (B100), petro-diesel (B0) and the fuel  
91 blends (B10-30) studied as a function of temperature. The Fig. ??a represents the study where the FPC was  
92 not added to the fuel while the FPC dosed fuel tests at a 1: 10 000 FPC to Fuel ratio are depicted on Fig. ??b.  
93 The collected data shows a linear decline in fuel density as the temperature increases irrespective of its blend  
94 formulation and catalyst dosage.

95 A fuel concentration packing order can be observed on both density plots where for blended fuel the reduction  
96 in biodiesel content translates results of reduced density. For instance, when referring to Fig. ??a, the density  
97 curve packing order is as follows: B100»B30>B20>B10>B0. Referring to Fig. ??a, the pure petro-diesel appeared  
98 to have lower density in comparison to the pure biodiesel by 6.08% when taking the mean of the resulting density  
99 range. Blending proved to generate a median density with respect to both biodiesel (B100) and petro-diesel (B0)

---

100 pure fuels as depicted on Fig 1 irrespective of the FPC dose investigated. To establish the line of fit, the fuel blend  
101 results were observed to be congruent with the work of Enweremadu et al (2011), whereby blend formulations  
102 data set followed the equation (1) that follows:  $\rho = AT + B$  (1)

103 Where  $\rho$  represents the density of the blend the temperature range, T ( $^{\circ}$ C) investigated. Taking a blend with  
104 common concentration of FPC undosed biodiesel blend of B20 in this study and the data was best modelled by  
105 equation (2) that follows:  $\rho = -0.0007T + 0.8696$  (2)

106 When equation (2) is used, the fitting curves produced a regression coefficient of  $R^2 = 0.9999$ . For the FPC  
107 dosed fuel, the data set followed the equation (3) that follows:  $\rho = -0.0007T + 0.8704$  (3)

108 The regression coefficient obtained from the line of fit was  $R^2 = 0.9999$ . It can be observed that the fuels  
109 showed equivalent values of "A" and minor deviation in "B" which was translated to a standard deviation of  
110 0.0005657. The summary of the fitting curve coefficients and  $R^2$  values are represented on Table 1. When  
111 comparing the complete data set of the FPC dosed and undosed fuel, a maximum standard deviation of was  
112 obtained as shown on Table 2. With regards to the values of the mean density for the FPC dosed fuel, one may  
113 deduce that the influence of the FPC on fuel density was insignificant for the studied samples as evidenced by  
114 the low standard deviation values.

## 115 10 b) Effect of FPC on fuel viscosity

116 Biofuel has been reported by numerous scholars to exhibit high viscosity as compared to petrodiesel (Franco Z.  
117 and Nguyen Q.D., 2011; Misra R.D. and Murthy M.S., 2011; Geacai S. et al, 2015). This often causes poor fuel  
118 atomization crucial for combustion in combustion chambers leading to injector chocking and the accumulation  
119 of carbon in the engines (Schwab A.W. et al., 1987). One solution often proposed is the efficient biodiesel-petro-  
120 diesel blend formulation which then leads to the attainment of acceptable flow properties as conducted in this  
121 work. On the Fig. 2, the viscosity data for the blend formulations presented in the previous section is depicted.  
122 It can be observed that fuel viscosity decreases with an increase in operating temperature for the both FPC dosed  
123 and undosed fuel. The relationship between viscosity and temperature for the data collected was discovered to  
124 follow a power fitting curve as in equation (3) that follows:  $\rho = cT^d$  (4)

125 Where  $\rho$  is the fuel viscosity (cP), c and d are the fitting curve coefficients. The summary of the fitting  
126 coefficients for the investigated fuels is displayed on can be deduced that the fitting curve represented by equation  
127 (3) can be used to predict the fuel viscosity as of the blends. The expected packing order exhibited on the density  
128 curves in previous section where the highest values were obtained at high biodiesel concentration was also realized  
129 on the viscosity curves as seen on Fig. 2.

130 The FPC dosed fuel blends followed a similar trend, with the curves approaching a similar value of 95.8 cP at  
131 80  $^{\circ}$ C. Having B30 approaching B20, more statistical analysis was needed to validate the presence of variance in  
132 the mean data sets of the FPC dosed and

## 133 11 c) Effect of FPC on fuel flash point

134 The flash point temperature of biodiesel is the minimum temperature at which the fuel will ignite (flash) in the  
135 presence of an ignition source. Flash point varies inversely with the fuel's volatility (Sivaramakrishnan and  
136 Ravukumar, 2012). Biodiesels have been reported to have higher flash and fire points than the petro-diesel by  
137 Odeigah Edith et al (2012). From the Table ??, it can be observed the flash point values generally increase with  
138 an increase in biodiesel concentration. When comparing the FPC undosed and dosed blends, the results showed  
139 a slight increase in flash point of B10 samples while at higher blend concentrations, the FPC dosage marginally  
140 lowered the flash point of all investigated blends. Nevertheless, the observed increase in flash point as blend  
141 concentration increases may be considered as good results with respect to safety and fuel handling requirements.  
142 At the same time having FPC lower the flash point marginally can be good for ignition of fuel in combustion  
143 ignition engines. This can be attributed to the observed reduction in fuel viscosity and density as discussed in  
144 the previous section, although the deviation is insignificant.

## 145 12 IV.

## 146 13 Conclusion

147 The results have revealed that at an FPC: Diesel fuel dosage ratio of 1: 10 000, the FPC did not have significant  
148 effects on both density and viscosity of the fuel when temperature was steadily increased from 20 $^{\circ}$ C to 80 $^{\circ}$ C. An  
149 increase in blend concentration resulted to an increase in flash point. This was considered as good safety feature  
150 for fuel handling purposes.

151 Finally, the results presented in this paper should not be presumed to be the final answer to properties studied  
152 in this work on the specific biodiesel- Table 3. From the regression coefficient values ( $R^2$ ), it is a function of  
153 temperature since  $R^2 > 0.96$  for the majority undosed fuels. A comparative study of the FPC dosed and undosed  
154 fuels depicted on Table ?? shows that there is variance in the means of viscosity since ANOVA ( $n=13$ ,  $P=0.05$ ) F  
155 test value of 494.140 is greater than F crit of 2.604, requiring further t-Test analysis assuming unequal variance  
156 between the two data sets of  $n=13$  each. From the Table ??, the difference between the B30 sample means of  
157 134.6297 and 132.759 cP for the FPC undosed and dosed fuels respectively can be observed. The significance of

## 13 CONCLUSION

---

158 the standard deviation (Std. Dev) of 1.3228 was investigated using the t-Test. The statistical analysis showed a  
159 t stat value of 0.1466 which is greater than the t critical value of 2.064 and this justify that there was no need  
160 to reject the null hypothesis as the observed difference between the mentioned sample means is not convincing  
enough to conclude that the average viscosity values differ significantly. The comparative study on Table ?? <sup>1</sup>



Figure 1:

1

Year 2015

4

IV Version I

e XV Issue

( ) Volum J

Global Journal of Researches in Engineering

SO 2

F crit R 2 -

t stat t crit

V.

-

Figure 2: Table 1 :

161

2

FUEL BLEND	UNDOSED FUEL Density (g/cm <sup>3</sup> )	Density (g/cm <sup>3</sup> )	FPC DOSED FUEL	COMPARATIVE Std. Dev.
B100	0.8674	0.8677		2.7305x10 <sup>-4</sup>
B30	0.8381	0.8381		3.6262x10 <sup>-6</sup>
B20	0.8353	0.8350		1.9001x10 <sup>-4</sup>
B10	0.8305	0.8309		2.4549x10 <sup>-4</sup>
B0	0.8171	0.8169		1.2293x10 <sup>-4</sup>

Figure 3: Table 2 :

3

FUEL BLEND	UNDOSED FUEL Coefficients			FPC DOSED Coefficients		
	C	d	Regression R <sup>2</sup>	c	D	Regression R <sup>2</sup>
B100	1573.10	-0.580	0.9922	1397.10	-0.551	0.9903
B30	971.12	-0.522	0.9846	1140.90	-0.569	0.9767
B20	860.73	-0.508	0.9811	823.53	-0.489	0.9844
B10	879.95	-0.519	0.9766	812.27	-0.492	0.9821
B0	697.41	-0.485	0.9936	718.68	-0.478	0.9930

Figure 4: Table 3 :



.1 Acknowledgements

162 The Author would like to thank the Technology Innovation Agency of Tshwane University of Technology for  
163 their financial support, the Technology Station in Chemical -GaRankuwa for their Research Centre, Matayo  
164 Biodiesel Producers for their samples, Fuel Technology Pty Ltd in Western Australia for support and the Fuel  
165 Performance Catalyst used in this work and finally, the following students: Kenny Lesetja Mokgotlwa, Olivier  
166 Kapya, Daphney Hlotse, Phakamani Mahlangu and Sello Machaba for experimental support. Lastly, Cebolenkosi  
167 Ntuli for his technical assistance.  
168

169 [Balat and Balat ()] ‘A critical review of biodiesel as a vehicular fuel’. M Balat , H Balat . *Energy Conversion*  
170 *and Management* 2008. 89 p. .

171 [Kivevele and Huan ()] ‘An Analysis of Fuel Properties of Fatty Acid Methyl Ester from Manketti 10’. T Kivevele  
172 , Z Huan . *Seeds Oil. International Journal of Green Energy* 2015. 12 p. .

173 [Avanish et al. ()] *Bio-diesel-A global scenario. Renewable and sustainable energy reviews*, A Avanish , D  
174 Subramaniam , A Murugesan . 2014. 29 p. .

175 [Mobida et al. ()] *Biodiesel production from baobab (Adansoniadigitata L.) seed kernel oil and its fuel properties.*  
176 *Industrial crops and products*, E Mobida , P Osifo , H Rutto . 2014. 59 p. .

177 [Zhang et al.] *Biodiesel production from waste cooking oil*, Y Zhang , M A Dubé , D D Mclean , M , Kates .

178 [Sivaramakrishnan ()] ‘Determination of cetane number of biodiesel and its influence on physical properties’. K  
179 Sivaramakrishnan , P , Ravikumar . *Journal of Engineering and Applied Sciences* 2012. 2 (6) p. .

180 [Green Cape ()] *Developing a business case for sustainable biofuels in South Africa: A focus on waste-based*  
181 *bioethanol for fleet transport in the Western Cape*, Green Cape . 2013.

182 [Pradhan and Mbohwa ()] ‘Development of biofuels in South Africa: Challenges and opportunities’. A Pradhan  
183 , C Mbohwa . *Renewable and Sustainable Energy Reviews* 2014. 39 p. .

184 [Odeigah ()] ‘Factors affecting the cold flow behaviour of biodiesel and methods for improvement-A review’. E  
185 Odeigah , JB , Ramfiel , Y , Robiah . *Pertanika J. Sci. & Technol* 2012. 20 p. .

186 [Franco and Nguyen ()] ‘Flow properties of vegetable oil-diesel fuel blends’. Z Franco , Q D Nguyen . *Fuel* 2011.  
187 90 p. .

188 [Enweremadu ()] ‘Investigation of the relationship between some basic flow properties of shea butter biodiesel  
189 and their blends with diesel fuel’. C C Enweremadu , HL , Rutto , JT , Oladeji . *International Journal of the*  
190 *Physical Sciences* 2011. 6 p. .

191 [Geacai et al. ()] ‘Measurement, correlation and prediction of biodiesel blends viscosity’. S Geacai , O Lulian , I  
192 Nita . *Fuel* 2015. 143 p. .

193 [Misra and Murthy ()] ‘Performance, emission and combustion evaluation of soapnut oildiesel blends in a  
194 compression ignition engine’. R D Misra , M S Murthy . *Fuel* 2011. 90 p. .

195 [Schwab et al. ()] ‘Preparation and properties of diesel fuels from vegetable oils’. A W Schwab , M O Bagby , B  
196 Freedman . *Fuel* 1987. 66 (10) p. .

197 [Process design and technological assessment] *Process design and technological assessment*, (ess design and  
198 technological assessment) 89 p. .

199 [Enweremadu ()] ‘Technical aspects of production and analysis of biodiesel from used cooking oil-A review’. C C  
200 Enweremadu , MM , Mbarawa . *Renewable and Sustainable energy Reviews* 2009. 13 p. .

201 [Mosesane et al. ()] ‘The effect of a Homogeneous Combustion Catalyst on Diesel Consumption in South African  
202 Engines’. M J Mosesane , R K Mbaya , L Kalombo , Tshabalala . *International Journal of Automotive*  
203 *Engineering and Technologies* 2015. p. .

204 [Yuan et al. ()] ‘The Specific Gravity of Biodiesel Fuels And Their Blends With Diesel Fuel’. W Yuan , A C  
205 Hansen , Q Zhang . *Journal of Scientific Research and Development. Manuscript EE* 2004. 04 p. .