

Experimental Study on Effect of Concrete Made with Textile Effluent and Treated Effluent Water

S.Purusothaman¹ and P.Vignesh²

¹ THE KAVERY ENGINEERING COLLEGE

Received: 13 December 2016 Accepted: 3 January 2017 Published: 15 January 2017

Abstract

This paper deals with study of possible utilization of textile water in concrete by analyzing their durability properties. The basic properties of different stages of effluent such as raw effluent, anaerobic process outlet, and tertiary treated outlet, reverse osmosis feed effluent from the textile industry were tested and the results were found to be satisfactory such that it can be used for construction purposes. By using the four stages of treated effluent, concrete specimens were casted and tested for its mechanical properties (compressive strength and tensile strength) and the results were found to be optimum for anaerobic and tertiary treated outlet. Hence the study was planned to continue for durability properties (Acid attack-sulphuric acid, hydrochloric acid and carbonation) of specimens using anaerobic and tertiary effluent.

Index terms—

Due to urbanization and expanding economic activities, about 13% of the world's population do not have access to safe drinking water. With current trend of water demand, water shortage will become even more intense and approximately, half of the world's population will suffer from major water scarcity by the year 2030 said by UNESCO. Industrial sector, contributes about 20% of the national income. Textile industry contributes nearly 14% of the total industrial production in India. There are about 10,000 garment manufactures and 2100 bleaching and dyeing industries in India. Textile waste water includes a large variety of dyes and chemical additions that pose an environmental challenge for textile industry not only as liquid waste but also due to its chemical composition. The shifting of irrigation water to fulfil the need of industrial use as well as water quality and lowering of water table around. The surface as well as ground water quality induces environmental degradation over long period of time because of discharge of highly contaminated effluent accelerated by over exploitation of existing water resources. The world bank estimates that 17 to 20 percent of industrial water pollution comes from textile dyeing and finishing treatment given to fabric majority are concentrated at Tirupur and Karur in Tamil Nadu, Ludiyana in Punjab and Surat in Gujarat. In recent decades, major research project are undergone to develop the utilisation of industrial waste into useful one.

1 D

Auhtor : The Kavery Engineering College Mecheri. e-mails: s.purusothcivill@gmail.com, pvigneshcivill29@gmail.com, jayabalce4@mail.com

2 Conclusion

This study shows the possible utilization of textile water in making concrete cubes with good and equivalent strength of concrete cubes made with potable water. Compressive strength of concrete cubes made with TETW and TEW was good and equivalent to potable water. The behavior of acid attack on concrete cubes made with TEW was less compare to the potable water.

2 CONCLUSION

42 ? Further durability studies are needed and planned to know the durability properties in detail ? The study
43 can be further extended as study of chemical nature of the sludge by undergoing several periodic analyses on
44 sludge produced in different chemical processing industries, leachability and toxicity analysis on the sludge and
45 sludge bricks, and other applications which can utilize sludge. ^{1 2 3}

¹Year 2017

²© 2017 Global Journals Inc. (US)

³. Aathira G Krishna, Jerry Anna Mathew et al (2013) 'Modelling of Chemical Durability Parameter of Fly ash Blended Concrete' International Journal of Scientific & Engineering Research Volume 4, Issue 8

Experimental Study on Effect of Concrete Made with Textile Effluent and Treated Effluent Water

GlobalIV. a) Tests For Cement Testing of Material ? Ordinary or low heat Portland
Jour- cement conforming to IS:269-1976 ? RAMCO 53 grade ordinary Portland
nal cement (OPC) is used for the study programme. i. Setting time test (Vicat
of apparatus) ? Initial Setting Time ? Lower the needle gently and bring it
Re- in contact with the surface of the test block and quick VI. Test for Fresh
searchesConcrete ? A concrete Mix of M 30 filled in the three layers compacted
in with tamping rod. ? Top surface is leveled and mould is raised vertically. ?
En- The slump which is the difference In height a) Slump Cone Test c) Flexural
gi- Strength Concrete in Prism Sl. no Age of test Conventi onal Concrete 1 7
neer- 10.1 2 14 12 between the top mould and the highest point on the subsided
ing concrete measured. 3 28 14.56 The sulmp observed = 25 cm release. Initial
() Setting time = 20 min ? Final Setting Time ? Replace the needle of vicat
Vol- apparatus by a circular attachment. Final Setting time = 10 hrs ii. Specific
ume gravity of sand = 2.68 ii. Sieve Analysis ? Arrange the sieve set in orders of
XVII 4.75mm,2.36mm,1.18mm,1mm, 600 μ ,300 μ ,150 μ size and a pan at the bottom.
Is- b) Compaction Factor Test ? The inner surface of the hopper and cylinder
sue are greased. The weight of empty cylinder with its base (W1 gm) is taken.
I 12 14 16 10 VII. ? Compressive strength ? Split tensile strength ? Flexural
Ver- strength a) Compressive Test For Concrete In Cube 0 5 10 15 20 25 30 35
sion 7 days 14 days 28 days conventional concrete Textile Treated Effluent water
I 12 Tetile Effluent water Sl. no Age of test Conventio TEXTILE ? The test
Year sample is subjected to a total of 15 below with a time interval of not less than
2017 one second. The aggregate impact value = 13.23% c. Crushing Strength Test
E ? The test sample consists of aggregate, the whole of which passes 12.5mm
Year sieve and retained on 10mm sieve. ? The test sample is added in thirds,
2017 each thirds is tamped by equally distributed strokes of tamping rod. The
Globaldepth of the aggregate in the TREATED EFFLUENT WATER TEXTILE
Jour- EFFLUENT WATER 10.5 9.4 ? ? The top surface of the cylinder is levelled
nal and the 12.6 11.8 outside of the cylinder is wiped and weighted with 14.8 14.4
of concrete (W 3 gm) The compaction factor = 0.8 cylinder is about 10cm. ?
Re- The loaded at a uniform rate in such a way that a total load of 400KN is
searchesreached in 10 minutes. Conventional Concrete ? The load is released and the
in whole of the material is removed from the cylinder. ? The removed material
En- from the cylinder is sieved on 2.36mm sieve for the fraction passing the sieve
gi- is weighed. The aggregate crushing value = 17.7% d. Flakiness Index Test: ?
neer- Each fraction is gauged in turn for thickness gauge. The separate aggregate
ing fractions are passed through the corresponding slots in the thickness gauge
(E as indicated in the table. ? The weight of aggregate passing through each
) of the slot is determined. Flakiness index= 31.02% V. Mix Design Given
Vol- Specificgravity of cement= 3.15 Specificgravity of coarse aggregate= 2.90
ume Specificgravity of fine aggregate= 2.68(ZONE 3) Degree of workability= 0.90
14 CF W/C ratio = 0.38 TARGET MEAN STRENGTH OF CONCRETE (fck)
XVII Fck = 39.9N/mm² 0 1 2 3 4 5 7 days 14 days28 days Conventional TEXTILE
Is- TREATED EFFLUENT WATER nal Concrete TEXTILE TREATED EF-
sue FLUENT WATER TEXTILE EFFLUENT WATER 1 7 2.83 3.0 2.63 2 14
I 3.25 3.29 3.1 3 28 3.88 3.92 3.78 Concrete Cylinder Strength Test b) Splitting
Ver- Tensile Strength For Concrete In Sl.no Conventional Concrete TEXTILE
sion TREATED EFFLUENT WATER TEXTILE EFFLUENT WATER 1 7 20
I 21.6 19.8 2 14 22.67 24.72 21.54 3 28 27.18 29.30 26.57 Age of test 0 2 8
TEXTILE TREATED 6 EFFLUENT WATER 4 7 days 14 days 28 days
TEXTILE EFFLUENTWATER V.11.

[Note: Specific Gravity of Cement ? Take a clean dry pycnometer with its cap and weight it. (M 1g)Take about 200g of dry cement in the pycnometer and find the weight of pycnometer with cement. (M 2g) Specific

-
- 46 [Kumar and Chaudhary ()] ‘Adsorption of reactive red 194 dye from textile effluent by using class F fly ash’.
47 Atul Kumar , Pratibha Chaudhary . *Sci* 2013. 1 (2) p. .
- 48 [Kanitha ()] ‘Potential utilisation of untreated/treated textile effluent in concrete’. Ramya M Kanitha . *Interna-*
49 *tional Journal of Research in Engineering* 2014. p. .