# Global Journals LATEX JournalKaleidoscope<sup>TM</sup>

Artificial Intelligence formulated this projection for compatibility purposes from the original article published at Global Journals. However, this technology is currently in beta. *Therefore, kindly ignore odd layouts, missed formulae, text, tables, or figures.* 

# Evaluation of Dye Bio-Sorption Properties of Sphagnum Cymbifolium (Moss) in Aqueous Solution by the Batch Process

Idika Digbo<sup>1</sup>, Oguzie, E.E<sup>2</sup>, Ogukwe, C.E<sup>3</sup> and Victor Njoku<sup>4</sup>

<sup>1</sup> Babcock University

Received: 15 December 2020 Accepted: 3 January 2021 Published: 15 January 2021

#### 7 Abstract

3

5

Objective: One of the major objectives of this research work is to expand the field of 8 application of natural biomass for the treatment of dye based industrial effluents. It is also a aimed at studying the effect contact time, initial dye concentration, pH, temperature, 10 dissolved salts on the bio-sorption properties of sphagnum cymbifolium(moss) on to methylene 11 blue dye by the batch process. Methods: The biomass was characterized by scanning electron 12 microscopy (SEM) in order to examine the surface morphology of the biomass. The screened 13 biomass samples were characterized at 1000 x magnification, 500 x magnification and 200 x 14 magnification for their surface morphologies, This was done using a scanning electron 15 microscope (FEI â??" inspect/ OXFORD INSTRUMENTS â??" X- MAX), which was 16 equipped with an energy dispersive X- ray (EDAX) spectrophotometer employed for elemental 17 composition analysis. It was equally characterized with Fourier transformed infrared 18 spectroscopy (FTIR) spectrophotometer (Perkin â??" Elmer, England) in the wavelength 19 range of 350 â??" 4000nm. Methods: The biomass was characterized by scanning electron 20 microscopy (SEM) in order to examine the surface morphology of the biomass. The screened 21 biomass samples were characterized at 1000 x magnification, 500 x magnification and 200 x 22 magnification for their surface morphologies, This was done using a scanning electron 23 microscope (FEI -inspect/ OXFORD INSTRUMENTS -X-MAX), which was equipped with 24 an energy dispersive X-ray (EDAX) spectrophotometer employed for elemental composition 25 analysis. It was equally characterized with Fourier transformed infrared spectroscopy (FTIR) 26 spectrophotometer (Perkin -Elmer, England) in the wavelength range of 350 -4000nm. 27

29

<sup>28</sup> 

Index terms—bio-sorption, sphagnum cymbifolium, batch process, sem.

Abstract-Objective: One of the major objectives of this research work is to expand the field of application of natural biomass for the treatment of dye based industrial effluents. It is also aimed at studying the effect contact time, initial dye concentration, pH, temperature, dissolved salts on the biosorption properties of sphagnum cymbifolium(moss) on to methylene blue dye by the batch process.

Methods: The biomass was characterized by scanning electron microscopy (SEM) in order to examine the surface morphology of the biomass. The screened biomass samples were characterized at 1000 x magnification, 500 x magnification and 200 x magnification for their surface morphologies, This was done using a scanning electron microscope (FEI -inspect/ OXFORD INSTRUMENTS -X-MAX), which was equipped with an energy dispersive X-ray (EDAX) spectrophotometer employed for elemental composition analysis. It was equally characterized with

Fourier transformed infrared spectroscopy (FTIR) spectrophotometer (Perkin -Elmer, England) in the wavelength
 range of 350 -4000nm.

Results: Results for the biomass surface morphology obtained through the scanning electron microscopy (SEM)
 showed the presence of pores. These pores represented sites where dye molecules could be trapped in the course

#### 4 CHARACTERIZATION OF THE BIO-SORBENT

of the adsorption. The results from the Fourier Transformed spectroscopy (FTIR) after adsorption show that
C-H, C?H, and C?C, functional groups were responsible for the adsorption. The adsorption of methylene blue
dye was found to be dependent on contact time, biomass dose, pH, temperature and effects of dissolved salts.

Conclusion: From the results obtained, it is clearly seen that methylene blue can absorb onto sphagnum

cymbifolium(moss). It was equally discovered that all these variables contact time, biomass dose, pH,
temperature and the presence of dissolved salts affected the rate of adsorption of methylene blue onto sphagnum
cymbifolium(moss). In each of the analyses, three different experiments were performed, and the mean values

50 respected with their standard deviations.

## 51 1 INTRODUCTION

io-sorption can be defined as the abstraction of organic and in-organic species. This may include dyes, metals,
 and odor causing substances using live or dead biomass or their derivatives. The above can be achieved either
 through the batch or fixed bed technique.

55 But, this research work is aimed at achieving it through the batch process.

The batch process of adsorption occurs as a result of agitation between the biomass and the dye solution. Such agitation is normally provided by a shaker or a magnetic sterner.

Synthetic dyes which include a wide range of aromatic water soluble dispersible organic colorants are used extensively in textile industries. Effluents containing synthetic dyes not only produce visual pollution, but also are hazardous to ecological systems and public health.

Conventional treatments of dye containing effluents are either in effective, costly, complicated or have sludge disposal problems [1].

Robinson etal [2] reviewed the current treatment technologies including bio-sorption with proposed alternatives for the removal of dyes in textile effluents.

<sup>65</sup> Due to the increasing stringent restriction on pollutant contents of industrial effluent. Due to the increasing <sup>66</sup> stringent restriction on pollutant contents of industrial effluents, it becomes very important to remove dyes from

waste water before they are discharged the environment many low cost adsorbents including natural materialsfrom industries and agriculture have been proposed by several workers [3,4].

Some researchers reported the use of plant leaf biomass to adsorb heavy metals from solutions [5][6][7]. Limited work was reported on the bio-sorption of cationic azo dyes and other reactive dyes on fresh water algae [8,9]. This work is carried out with the view of expanding the field of application of natural biomass for the treatment of dye waste waters, and also determine the adsorption capacity of sphagnum cymbifolium (moss) on to methylene blue dye. Since such an indepth study has not been done on this biomass, the results obtained from the work

vill add to the expansion of knowledge in this area.

## 75 2 MATERIALS AND METHODS

76 The methylene blue dye used in these investigations were obtained from qualikem laboratory, owerri Nigeria.

Other necessary laboratory, Owerri Nigeria. Other necessary laboratory chemicals used were equally obtainedfrom this laboratory.

The sphagnum cymbifolium (moss) used was obtained from ikorodu area in Lagos, Nigeria which is located within the following coordinates 6.6194°N and 3.5105°E. This sample was identified at the department of crop science at the federal university of technology, owerri, Nigeria with the voucher specimen number of FUT/CR/005/16.

The biomass was washed severally with distilled water to remove any dirt from it. The washed biomass was air dried for ten days until a constant weight was obtained. The biomass was grinded with a new sonic domestic blender to avoid any form of contamination. It was screened using 600-850 micro sized sieves and stored in air tight containers ready for adsorption.

The methods and techniques employed in these determinations are the standard methods which have been used by other researchers [10,11].

## 89 **3 III.**

## 90 4 CHARACTERIZATION OF THE BIO-SORBENT

91 The surface structure and morphology of the sphagnum cymbifolium (moss) was characterized at 1000X 92 magnification, 500X magnification and 250X magnification respectively for their surface morphology. This was 93 done using scanning electron microscopy (SEM) (FEI-Inspect oxford instrument-x-max) which was equipped with 94 an energy dispersive x-ray (EDAX) spectrophotometer employed for elemental composition analysis.

The biomass sample was further characterized for their fundamental functional groups before and after adsorption experiment using a Fourier Transformed Infrared (FTIR) spectrophotometer (Perkin-Elmer, England) in the wave length range of 350-4000nm using KBr powder and fluk a library for data interpretation.

### <sup>98</sup> 5 a) Effect of Contact Time

Experiments were carried out by mixing 40mg of the biomass in a dye solution of 90mg/L. Agitations were made using a shaker at the range of 30-180 minutes at 250rpm. After the shaking, the sample was taken and centrifuged. The left out solution was analyzed for dye absorbance at 600nm in au.v spectrophotometer. These tests were carried out in triplicates and mean values with their standard deviations reported.

#### <sup>103</sup> 6 b) Effect of biomass dose

Experiments were carried out by mixing biomass of different doses (10-100mg) with a dye solution of concentration 90mg/L. Agitations were made for three hours in a shaker at 250rpm. The left out solution was centrifuged and subsequently analyzed in au.v spectrophotometer at 600nm.

## $_{107}$ 7 c) Effect of ph

Experiments were carried out by mixing 40mg of the biomass in a 90 mg/L dye solution at different pH range (2)(3)(4)(5)(6)(7)(8)(9)(10)(11). After three hours of agitation in a shaker at 250rpm, the samples were centrifuged. The left out supernatant solution was analyzed in au.v spectrophotometer for dye absorbance at 600nm.

#### <sup>112</sup> 8 d) Effect of dissolved calcium chloride

Experiments were carried out by mixing 40mg of the biomass in a 90mg/L dye solution with varying amount of dissolved calcium chloride (0.10-0.20M). After three hours of agitation in a shaker at 250rpm, the samples were centrifuged and the left out supernatant solution analyzed for dye absorbance in au.v spectrophotometer at 600nm.

#### <sup>117</sup> 9 e) Effect of temperature

Experiments were carried out by mixing 40mg of biomass in a 90mg/L dye solution in a vessel placed in a magnetic hot plate. This was done in batches with the aid of a thermometer for the proper monitoring of the temperature. The temperature range was between (323-353K). After three hours of agitation in the hot plate at 250rpm, the samples were centrifuged, and the super natant solution analyzed for dye absorbance in au.v spectrophotometer at 600nm. The FTIR spectrum of Sphagnum cymbifolium (moss) after adsorption as shown in figure 5 above was used to ascertain the functional groups that were responsible for the adsorption reaction.

## 124 10 Results and Discussion

The spectrum showed prominent peaks at 3406nm (-OH, -NH), 1642nm and 1429nm which are characteristic of the -CO functional group which strongly predict the presence of carboxylic acid group in the biomass with the adsorbed dye molecule. After the adsorption, there were some bond displacement of the original peaks indicating the functional groups that were responsible for the adsorption reactions. The displacements occurred at 2925.71nm and 2363.57nm which correspond to these functional groups, C-H, C?N, and C?C.

Furthermore, although the intensity of the peaks greatly decreased after the adsorption, the functional groups 130 on the biomass did not disappear totally during the biomass characterization after the adsorption. This indicates 131 that the interaction of the dye molecules with the sphagnum cymbifolium was merely a physical process. As could 132 be seen from figure 6, a two stage kinetic behavior is observed. A rapid initial adsorption over thirty minutes, 133 followed by a longer period of much slower uptake as could be seen from figure 6 above. At the beginning 134 135 of the adsorption, the value of q e increased quickly, then 150 minutes later, the change became slow. Here, the reaction is assumed to have reached equilibrium. It was observed that the percentage removal efficiency of 136 the biomass increased significantly when the biomass increased significantly when the adsorbent dose increased 137 from ??10-40mg). The value of qe above is that the adsorption sites remained unsaturated and the number of 138 sites available for adsorption increased by increasing the adsorbent dose up to the adsorbent dose of 40mg. At 139 higher adsorbent concentration, there is a fast superficial adsorption onto the adsorbent surface than when the 140 adsorbent dose is lower. Thus, with increasing the adsorbent dose, the amount of dye adsorbed per unit mass 141 of the adsorbent is reduced. A similar trend was previously reported by other researchers [13,14]. The rate of 142 adsorption was found to be dependent on pH. A pH of 4 favored the maximum adsorption of the dye onto the 143 biomass as could be seen in figure 8. Several reasons may be attributed to the dye adsorption behavior of the 144 sorbent relative to the large number of active sites, and also the chemistry of the solution. At very low pH values, 145 the surface of the adsorbent would be surrounded by hydrogen ions which compete with dye ions binding sites 146 147 of the sorbent. At high pH values, the surface of the leaf particles may be negatively charged which engaged 148 the positively charged dye cations through electrostatic forces of attraction. Similar situation were reported by other researchers. ??vennapusaetal 2008). As could be seen from the figure 9, the equilibrium uptake increased 149 with the increase of initial dye concentration at the range of experimental considerations. This is as a result of 150 the increase in the driving force from the concentration gradient. In the same conditions, if the concentration of 151 the dye in solution was bigger, the active sites of the biomass will be surrounded by much more dye ions. The 152 process of adsorption would carry out more sufficiently. So, the values of q e increased with the increasing of 153

initial dye concentrations. Other studies have revealed the same pattern of result about initial dye concentration.

??vennapusaetal 2008). Figure 10 shows the effect of temperature on adsorption. It was observed that the value of q e decreased with increase temperature. This could suggest that the adsorption process may be a physical process. A similar trend was observed by other researchers.

 $0.06\ 0.08\ 0.10\ 0.12\ 0.14\ 0.16\ 0.18\ 0.20\ 0.22\ 0.24\ 0.0\ 0.5$  Figure 11 shows the effect of dissolved calcium chloride on q e. The waste water containing dye has commonly higher salt concentration. The effects of ionic strength are of some importance in the study of dye adsorption onto biomass. It was seen that the increase in salt concentration resulted in the decrease of the values of q e, and the percentage removal efficiency. This trend indicated that the adsorbing efficiency decreased when calcium chloride concentration increased in the dye solutions. This could be attributed to the competitive effect between the ions and the cations from the salts for sites available for the salt increased from 0.10m to 0.20m, the q e values decreased to lower values.

#### 165 11 CONCLUSIONS

<sup>166</sup> From the experimental results, sphagnum cymbifolium (moss) could act as a good bio-sorbent for the removal of

methylene blue dye in aqueous solutions. It was equally observed that lower pH value favored the adsorption of
 methylene blue dye onto the biomass. The values of q e were found to be dependent on the solution pH, biomass
 dose, contact time, salt concentration and initial dye concentration.



169

Figure 1: B

<sup>&</sup>lt;sup>1</sup>© 2021 Global Journals

 $<sup>^2 \</sup>rm Evaluation$  of Dye Bio-Sorption Properties of Sphagnum Cymbifolium (Moss) in Aqueous Solution by the Batch Process © 2021 Global Journals V.



Figure 2: lobal





Figure 3: Fig. 1 :Fig. 2 :Fig. 3 :



Figure 4: Fig. 4 :



Figure 5: Fig. 5:

#### Figure 6:

#### 11 CONCLUSIONS

- 170 [Abraham ()], R Abraham. Environmental Chemistry of Chemical technology 1993. Wiley. 8 p. .
- 171 [Crini ()], G Crini . 2005.
- 172 [Vannapusa ()], R Vannapusa. 2008.

[Khattri and Singh ()] 'Adsorption of basic dyes from aqeous solution by natural adsorbent'. S Khattri , M Singh
 *Indian Journal of Chem. Technol* 1999. 6 (2) p. .

- [Kumar ()] 'Adsorption of malachite green onto Pitophora sp. A Fresh water algae/Equilibrium and kinetic
   modeling'. K Kumar . Journal of process biochem 2005. 40 p. .
- [Gosh and Bhatta Chrya ()] 'Adsorption of Methylene blue onto Kaolinite'. D Gosh , K Bhatta Chrya . Journal
   of App. Clay Sci 2002. 20 p. .
- IIdika et al. ()] Batch and fixed bed comparative study on the bio-sorption, Digbo Idika, I Ndukwe Nelly, C,
   Ogukwe Cynthia, E. 2019.
- 181 [Idika et al. ()] Batch and fixed bed comparative study on the dye bio-sorption properties of Cedruslibani (Elizabeth
- leaf) on methylene blue, bismarck brown y and indigo dye. The international journal of science and technoledge
  7, Digbo Idika , I Ndukwe Nelly , C , Ogukwe Cynthia , E . 2019. p. .
- [Low ()] 'Bio-sorption of basic dyes by waterhyacinth roots'. K Low . Journal of Biore Sour Technol. 52. P 1995.
   p. .
- <sup>186</sup> [Idika et al. ()] Bio-sorption properties of Sphagnum cymbifolium (moss) on methylene blue, Bismarck brown y, and indigo dues by the batch process. acta SATECH 11, D I Idika, C A Ogukwe, E E Oguzie, A O
- y, and indigo dyes by the batch process.
  Alishinloye, A Adewunmi. 2019. p. .
- [El-Geundi ()] 'Colour removal from textile effluent by adsorption techniques'. S El-Geundi . Journal of water
   Res 1991. 25 p. .
- 191 [Idika et al. ()] 'Effect of flow rate and bed height on the fixed bed adsorption of methylene blue dye, Bismarck
- brown y and indigo dyes onto Sphagnum cymbifolium (moss)'. D I Idika, N A Ndukwe, C E Ogukwe. IOSR
  journal of applied chemistry 2020. 13 p. .
- [Itan ()] 'Equilibrium Isotherm for lead ions on Chaff'. R Itan . Journal of hazard matter P 2005. p. .
- [Vadivehan and Vasanth ()] 'Equilibrium Kinetics, Mechanism, and process design for the sorption of methylene
   blue onto rice husk'. V Vadivehan, K Vasanth . Journal of Colloid inter sci 2005. 286 p. .
- [Gupta ()] 'Equilibrium uptake and sorption dynamics for the removal of a basic dye (basic red) using low cost
   adsorbents'. V Gupta . Journal of colloid interface science P 2003. p. .
- 199 [Evaluation of Dye Bio-Sorption Properties of Sphagnum Cymbifolium(Moss) in Aqueous Solution by the Batch Process]
- Evaluation of Dye Bio-Sorption Properties of Sphagnum Cymbifolium(Moss) in Aqueous Solution by the
   Batch Process,
- [Hjorth ()] 'Expanded bed adsorption in industrial bio Processing -recent development'. R Hjorth . P. 230. Journal
   of trends in biotechnology 1997. 15 (6) .
- [Guibal ()] 'Interactions of metal ions with chitosan based sorbent a review'. E Guibal . Journal of separation and purification Technol 2004. 38 p. .
- [Waranusatigul ()] Kinetics of basic dye (methylene blue) bio-sorption by giant duck weed (spirodelaPolyrrhiza),
   P Waranusatigul . 2003. p. . (Journal of environ mental Pollution)
- [Gleason ()] 'Manual of Vascular Plants of North Eastern United States and adjacent Canada 2 nd ed'. Cronquist
   Gleason . P 1991. 60 p. 69.
- [Han (2006)] 'Removal of Methylene blue from Ciqeous solution by Chaff in batch mode'. R Han . Journal of
   hazard matter in Press, 2006. April, 2006.
- <sup>212</sup> [Idika et al. ()] 'Studies on the impact of flow rate and bed height on the fixed bed adsorption of methylene <sup>213</sup> blue dye, bismarck brown y dye and indigo dye onto Cedruslibani (Elizabeth leaf) biomass'. Digbo Idika,
- Nelly Ndukwe , Cynthia Ogukwe , Aleshinloyeabimbola Adewunmiaderike . International journal of chemistry
   research 2020. 4 p. .
- [Langmuir ()] 'The constitution and fundamental properties of solids and liquids'. I Langmuir . Journal of Am.
   Chem. Soc 1916. 38 p. .
- 218 [Ai-Subu ()] 'The interaction of Cypress (Cu Pressurs Sempervirens) Cino chona (Eucalyptus Longifolia), and
- Pine (Pinus helepenses) leaves on their efficacies for lead removal from aqeous solution'. M Ai-Subu . Journal
   of Environmental resource 2002. 6 p. .
- [Wang ()] 'The Physical and surface chemical characteristics of activated carbon and the adsorption of methylene blue from waste water'. S Wang . *Journal of colloid interfi Sci* 2004. 284 p. .
- [Amadurai ()] 'use of Cellulose based waste for adsorption of dyes from aqeous solution'. G Amadurai . Journal
   of hazard matter B 2002. 92 p. .
- [Cruz ()] 'using inbed temperatures for visualizing the concentration -front movement'. P Cruz . Journal of chem.
   Engr. Edu 2001. 35 (27) p. .