Artificial Intelligence formulated this projection for compatibility purposes from the original article published at Global Journals. However, this technology is currently in beta. *Therefore, kindly ignore odd layouts, missed formulae, text, tables, or figures.*

| 1 | Sclerocarya Birrea Plant Oil: A Potential Indigenous Feedstock |
|---|--|
| 2 | for Biodiesel Production in Botswana |
| 3 | Dr. Jerekias Gandure ¹ |
| 4 | ¹ University of Botswana |
| 5 | Received: 11 December 2011 Accepted: 2 January 2012 Published: 15 January 2012 |

7 Abstract

Exploring new feedstocks for biodiesel production is now receiving widespread attention 8 world-over. This paper presents experimental results on properties of celerocarya birrea plant 9 oil. Chemical properties analysis of birrea plant oil were performed using gas chromatograph 10 and mass spectrometer, while the engine performance tests were conducted on a variable 11 compression ignition engine. Parameters such as fuel consumption, engine torque and engine 12 brake power were recorded at different engine loads for pure diesel fuel and birrea plant oil. 13 The experimental results indicate that birrea plant oil offer immense potential as both fuel 14 and feedstock for biodiesel production. The performance characteristics of ignition 15 compression engine using birrea plant oil indicate that the optimum compression ignition 16 engine occurs at 60 17

18

19 Index terms— Birrea plant oil, straight vegetable oil (SVO), lipid composition, properties, Botswana.

²⁰ 1 INTRODUCTION

he quest for biofuel production in Botswana is derived from several factors including volatile oil prices, potential 21 for job creation, fuel security and economic diversification. The desire to establish national energy self-reliance 22 and to develop alternatives to finite fossil fuel resources have resulted in the development of fuel technologies that 23 are based on the use of renewable agriculture based materials as feedstocks. In the case of renewable fuels for 24 25 compression ignition (diesel) engines, the majority of efforts to date have focused on biodiesel, which consists of 26 alkyl esters of fatty acids found in agricultural acylglycerol -based fats and oils. Biodiesel can be produced from any material that contains fatty acids, whether bonded or free ??Vicente et al., 2004). Consequently, different 27 28 vegetable oils can be used as fuel or feedstock for biodiesel production depending on oil properties.

29 All vegetable oils and animal fats consist primarily of triglycerides (Srivastava and Prasad, 2000; Karmakaret al., 2010). Triglycerides have a three-Author ? ? : University of Botswana, Mechanical Engineering 30 Department. Private bag 0061, Gaborone, Botswana. Tel: 00267 3554421, Fax: 00267 3952309, E-mail: 31 gandurei@mopipi.ub.bw backbone with a long hydrocarbon chain attached to each of the carbons. The differences 32 between oils from different sources relate to the length of the fatty acid chains attached to the backbone and the 33 number of carbon-carbon double bonds on the chain. Most fatty acid chains from plant oils are 18 carbons long 34 with between zero and three double bonds (Misra and Murthy, 2010). Fatty acid chains with no double bonds 35 36 are said to be saturated and those with double bonds are unsaturated. The number of carbon atoms and double 37 bonds in each of the five most common fatty acid chains found in common oils and fats are shown in Table 1.

The presence of double bonds in the fatty acid chains has a significant effect on the properties of the methyl esters (Knothe, 2005). The deformation of the molecule caused by the double bonds inhibits the growth of the crystals and this lowers the methyl ester's freezing temperature. Saturated oils and fats tend to freeze at higher temperatures. Animal fats, hydrogenated vegetable oils, and some tropical oils such as palm oil and coconut oil contain approximately 35 -45% saturated fatty acids and may be solid at room temperature (Misra and Murthy, 2010). Fatty acid methyl esters (FAME) produced from such oils may gel at relatively high temperatures. The carbon-carbon double bonds in unsaturated oils and fats are prone to oxidation by oxygen in the air.

4 A) BIRREA PLANT OIL

This effect is severe when the bonds are conjugated (two double bonds separated by two single bonds) as is 45 the case for linoleic and linolenic acids. These fatty acids will oxidise 50-100 times faster than oleic acid with an 46 unconjugated double bond. Saturated fatty acids are not subject to this type of oxidative attack. The choice of 47 oil feedstock determines the resulting biodiesel's position in the trade-off between cold flow, oxidative stability, 48 and cetane number. Fatty acid methyl esters from more saturated feedstock will have higher cetane numbers 49 and better oxidative stability, but will have poor cold flow properties. Fatty acid methyl esters from oils with 50 low levels of saturated fatty acids will have better cold flow properties, but lower cetane number and oxidative 51 stability ??Refaat, 2009). 52

Engine performance profile generated using a straight vegetable oil as fuel is another important property. The 53 nature of fatty acids largely determines 2009; Moser et al., 2009). In addition, iodine value is another important 54 property with regards to the use of straight vegetable oil as fuel or feedstock for the production of biodiesel. 55 The iodine value indicates the degree of unsaturation of oil (number of double and triple bonds). It corresponds 56 to the number of grams of iodine absorbed by 100 g of oil. The more the oil is unsaturated, the higher is its 57 iodine value. As such, low iodine value (saturated oil) is propitious to good combustion (Sidibe et al., 2010). 58 Generally, saturated oils offer better combustion (short evaporation time, short ignition delay, fewer deposits) 59 60 than unsaturated oils. Overall, quality of combustion decreases with increase in degree of unsaturation.

61 Using straight vegetable oils in diesel engines is not a new idea. Rudolf Diesel first used peanut oil as a fuel 62 for demonstration of his newly developed compression ignition (CI) engine as far back as 1910 (Balat and Balat, 63 2008) Literature suggests that vegetable oils can substitute for mineral diesel if reduction in viscosity is achieved by blending it with diesel or by preheating. De Almeida et al (2002) used heated palm oil as fuel in a diesel 64 generator. The study revealed that carbon monoxide (CO) emissions increased at higher loads. This was due to 65 lack of oxygen at higher equivalence ratios. Palm oil nitrogen oxide (NO x) emissions were however relatively 66 lower than mineral diesel. Masjuki et al. (2001) used preheated palm oil to run a CI engine. Better spray and 67 atomization characteristics were obtained due to reduction in the viscosity of fuel due to the preheating processes. 68 69 Torque, brake-power, specific fuel consumption, exhausts emissions and brake thermal efficiency were reported to be comparable to those of mineral diesel Wang et al. (2006) also performed experiment on blended vegetable 70 oil with diesel. The authors reported higher exhaust gas temperature with very small variations in CO emission 71 levels and relatively low NO x as compared to diesel. 72

This work evaluated chemical properties and engine performance of birrea plant oil to assess potential for use 73 74 as fuel and feedstock for biodiesel production in Botswana. Birrea tree is indigenous to most parts of Southern 75 Africa. In Botswana, for example, it is widely distributed all over the country but concentrated in the north eastern part of the country, approximately 250 km north east of Gaborone, Botswana's capital city. The species 76 then covers a huge part of the Central district and Tshapong Sub district. At maturity, the plant (tree) can grow 77 up to approximately 10m tall with a sterm diameter of approximately 0.8 m and have several branches that bear 78 fruits during the rainy season (October to April). However, because of limited scientific data, the age of the birrea 79 plant (tree) from which plant oil used for this study was extracted is not covered in the present investigation. It 80 is the author's view that some of these plants could be as old as 70 years and above but they still bear fruits. 81 The tree grows in warm and dry climatic conditions, and produce oval fruits that turn pale yellow when ready 82 for harvesting. In Botswana the harvesting period usually starts from December to the end of March. The fruit 83 consists of a hard woody seed covered by pulp and juice which makes the fleshy part of the fruit. The hard seed 84 contains mostly two oil rich nuts (kernel) which can be eaten as a snack. There is now a worldwide trend to 85 explore wild plants for oil to augment the already existing sources of oil. The fact that the birrea tree grows 86 in drier parts where common oil seeds cannot thrive has stirred interest in it as a valuable source of biodiesel 87 feedstock. This has led to the evaluation of birrea nut oil as potential feedstock oil for biodiesel production. In 88 evaluating the potential use of oil for this purpose, the fatty acid profile plays an important role. 89

90 **2** II.

91 3 MATERIALS AND METHODS

⁹² 4 a) Birrea plant oil

The birrea plant oil used for the current study was purchased from Kgetsi Ya Tsie, a Community Trust located in 93 the eastern part of the country approximately 300 km east of Gaborone City. The primary objective of the trust 94 95 is to promote the economic and social empowerment of rural women in the Tswapong Hills of Eastern part of 96 Botswana, who extracts birrea plant oil mostly for cosmetic markets in Europe and America. Prior to the plant 97 oil extraction processes, individuals members of the trust harvest yellow birrea fruits and manually remove the 98 outer skin of the fruit. The hard woody seed is then dried under natural conditions for 6 to 8 weeks. The primary objective of drying the hard woody seed is to ensure that minimum force is applied on cracking the hard woody 99 nut cover and to minimise damage of the oil rich nut. When the drying process is considered to be complete, 100 the hard woody seeds are stored in a dry place followed by the cracking process. The cracking process is also 101 done manually by individual members of the trust group. After cracking, the nuts are collected to a central oil 102 pressing centre for oil extraction process. 103

In the present investigations birrea oil nuts from the Lerala village and communities within the out skirt of Lerala village approximately 300 km east of the Gaborone City was used to extract oil. The extracted oil was then bottled into a glass container, placed in a cooler box with ice gel and transported to the laboratory for chemical analysis as described in section 2.2.

¹⁰⁸ 5 b) Oil characterization

The composition of birrea plant oil was analysed using the Waters GCT premier Time of Flight (TOF) mass spectrometer (MS) coupled to the Agilent 6890N gas chromatograph (GC) system. The instrument has high sensitivity and fast acquisition rates. In (AMDIS) software package, (chemdata.nist.gov/massspc/amdis) was used for peak identification. AMDIS extracts spectra for individual components in a GC-MS data file and identifies target compounds by matching these spectra against a reference library, in this case the NIST library. AMDIS also allows creation of personal libraries where routine analyses of compounds is encountered.

115 6 Global

i. Gas Chromatograph Conditions 1 μ L of birrea plant oil sample extract was injected into the system using an auto-injector. The injector temperature was set at 260 0 C in the splitless mode. Helium was used as the carrier gas at a flow rate of 1ml/min. Separation was achieved using a 30 meter DB5 -MS column. The oven temperature was kept at the initial 100 0 C for 2 minutes, and then gradually increased from 100 0 C to 290 0 C at a rate of 10 0 C per minute. The total run time was approximately 35 minutes.

¹²¹ 7 ii. Mass Spectrometer Conditions

The mass spectrometer (MS) conditions that were employed were a positive polarity of electron ionization (EI), a source temperature of 180 0 C, an emission current of 359µA. Other MS conditions including electron energy, resolution were set by the system auto tune function. Detection was by the micro channel plate detector (MCP) whose voltage was set at 2700 V. The oil composition was identified and quantified using the NIST (2005) mass spectral library using a combination of the Masslynx acquisition /data analysis software and the AMDIS by NIST.

¹²⁸ 8 c) Engine performance analysis

The engine performance test was conducted on a TD43F engine test rig. The test rig is water cooled, four-stroke diesel engine that is directly coupled to an electrical dynamometer. In addition to the conventional engine design, the engine incorporates variable compression design feature which allows the compression ratio to be varied from 5:1 to 18:1.

To establish that engine operating conditions were reproduced consistently as any deviation could exert an overriding influence on performance and emissions results, the reproducibility of the dynamometer speed control set points were maintained within \pm 0.067 Hz of the desired engine speed. The experimental work began with engine run on pure diesel fuel. This was done to determine the engine's operating parameters which constitute the baseline that was compared with the subsequent case when the birrea plant oil was used as fuel. At the point of fuel change, the fuel lines were cleaned with pure diesel fuel and engine left to operate with the fuel under test for approximately 15 minutes to stabilise at its new condition before readings were recorded.

¹⁴⁰ 9 III.

141 10 RESULTS AND DISCUSSIONS a) Birrea plant oil charac-142 terization

Five birrea plant oil samples were tested to establish the chemical composition present. This was done by injecting oil sample into the GC-MS system in quantities and procedure specified in Section 2.2 in a systematic study. A reference sample prepared by AccuStandards was used to calibrate the equipment. The Fatty Acids detected from the five birrea oil samples were largely similar. For simplicity, average concentration levels of fatty acids detected are presented in table 2. Table 2 also shows a number of fatty acids recorded in birrea plant oil which were not present in the reference sample.

The Fatty Acid profile of birrea plant oil indicates a range of fatty acids and esters, the majority of which 149 were not found in the reference sample. The observation may be attributed to the uniqueness of this indigenous 150 and unknown plant oil. Olein 2-mono and Olein 1-mono fatty acids were identified as geometrical isomers of the 151 152 same compound. Oleic acid, 3-hydroxypropyl ester is very unique in that it is not found on the NIST library and 153 has generated a lot of interest to the authors for further research work. The fatty acid that was detected to be most abundant is Trans-Oleic acid but could not be quantified because of its absence from the reference sample. 154 The second highest peak detected is for Ethyl oleate (ethyl ester). Other compounds had substantial presence 155 which could improve if concentrated through processing. The composition of birrea oil recorded in this analysis 156 is largely consistent with results obtained by other researchers (Burger et al., 1987). As discussed in Section 1, 157 the fatty acid parameters that have the greatest impact on fuel properties are the average chain length and the 158

degree of unsaturation. To a large extend, fuel properties improve in quality with increase in carbon chain length 159 and decrease as the number of double bonds increase, except cold flow properties. According to Knothe (2005), 160 the optimal fatty acid profile that provides optimal fuel properties with relatively less adverse impact on the 161 environmental is a mixture consisting of methyl oleates, esters derived from palmitic, oleic, and decanoic acids. 162 The fatty acid mixture of birrea plant oil presented in table 2 is largely composed of these desirable compounds, 163 depicting characteristics of a good fuel. This stimulated the need to perform thermal performance of birrea plant 164 oil as fuel on a variable compression ignition engine. The performance results are presented and discussed in 165 Section 3.2. 166

b) Engine performance analysis 11 167

Prior to using birrea plant oil as fuel in the compression ignition engine, the oil was neutralised using sodium 168 hydroxide in order to minimize the possible effects of corrosion on engine parts. The oil was also filtered to 169 eliminate possible presence of suspended matter that could form carbon deposits in the engine during combustion. 170 The birrea plant oil was then used to power a variable compression ignition engine to test the engine performance 171 of the fuel. Engine performance tests were conducted for compression ratios 13:1 through 17:1. To enable 172 the main findings of the study to be identified clearly, only performance results for compression ratio 16:1 are 173 presented in Section 3.2.1. The results were compared with the results for pure diesel fuel of boiling point 422 K, 174 vapor pressure of 53 Pa, density of 860 Kg m -3 and cetane number of 48. The comparison was done on the basis 175 of engine torque, engine brake power, and specific fuel consumption as mentioned earlier. The experimental data 176 were collected as discussed in section 2.3, leading to the results presented in figure ??. 177

i. Engine Performance Results 12178

Typical results for the variation of the engine torque, brake power and specific fuel consumption for birrea plant 179 oil and pure diesel fuel for different engine load settings are shown in Figure ??. 180

There are several clear findings to be drawn from the data presented in figure ??(a) to (c). Firstly, the results 181 indicate that the engine torque, brake power, and specific fuel consumption recorded for D100 and BPO for 182 operation condition (compression ratio 16:1) compares favourably well. The data in figure ??(a) shows a steady 183 increase in engine torque for both D100 and BPO with increase in engine load between 30 and 60%. However 184 within the same operating window, BPO recoded relatively high engine torque compared with D100. However, 185 it is clear from the data presented in figure ??(a) that as the engine load increase from 60% the data recorded 186 for D100 shows a steady increase in engine torque while the data for BPO shows a slight decrease with increase 187 in engine load. 188

The results in figures 1(b) and (c) also demonstrate that the data recorded for BPO compares favourably well 189 with that for D100. The maximum variation in brake power of 0.63W was recorded at 90% engine load, while 190 the minimum variation of 0.06W was recorded at 60% of engine load, with D100 recording 5.06W. The trends 191 shown in figure ??(b) suggests that the optimum compression ignition engine performance using birrea plant oil 192 occurs at 60% engine load. The data shown in figure ??(c) reinforces this observation, which shows the specific 193 fuel consumption recorded for D100 and BPO. One of the most discernible trends connected to figure ??(c) is 194 that the variations in specific fuel consumption recorded for D100 and BPO between 30% and 60% do not show 195 any significant difference for the fuels under review. The minimum variation of specific fuel consumption between 196 30% and 60% engine load is 0.01g/kWh, while a maximum of 0.17g/kWh was recorded at the engine load of 90%. 197 Overall, the results in figure ?? indicate that birrea plant oil is a potential fuel. The relationship between fatty 198 acid profile and engine performance analysis results of birrea plant oil indicates potential of converting the same 199 plant oil into quality biodiesel. 200 IV.

201

CONCLUSIONS 13 202

An experimental study to examine the profile of free fatty acids found in birrea plant oil and compared against 203 those found in the reference sample has been described. The study also carried comparative tests using B100 204 and D100 to assess the engine performance. From the experimental results, it can now be concluded that. a) 205 Birrea plant oil has properties that can enable it to function as a biofuel in IC diesel engines. This implies that 206 transesterifying birrea plant oil under standard conditions may produce biodiesel of international biodiesel quality 207 standards. b) Trans-Oleic acid is the major fatty acid in birrea pant oil and is not found in reference sample 208 prepared by AccuStandard. This suggests that further investigations on the compositionsition of the same fatty 209 acid need to be carried out. Load (%) BPO D100 $^{-1-2}$ 210

¹© 2012 Global Journals Inc. (US) Sclerocarya Birrea Plant Oil: A Potential Indigenous Feedstock for Biodiesel Production in Botswana

²January 2012© 2012 Global Journals Inc. (US)



Figure 1:

1

The second most abundant free fatty acid detected was Ethyl Oleate which is an ethyl ester. Other free fatty acids detected are Oleic acid, 3-hydroxypropyl ester, Palmitic acid (methyl ester), Palmitic acid (ethyl ester), suggesting that the oil has strong characteristics required for biodiesel feedstock. c) The results prove that the performance of IC diesel engine using birrea plant oil is close to pure diesel fuel suggesting that such oil is a potential indigenous feedstock for biodiesel production in Botswana.

Figure 2: Table 1 :

Figure 3: Table 2 :

13 CONCLUSIONS

211 .1 ACKNOWLEDGEMENTS

- We acknowledge support of the University of Botswana, and the Ministry of Wildlife, Tourism and Environment who granted a research permit for this work.
- 213 who granted a research permit for this work.
- [Balat and Balat ()] A critical review of biodiesel as a vehicular fuel. Energy conversion and management, M
 Balat , H Balat . 2008. 19 p. .
- [Aluyor et al. ()] Biodegradation of vegetable oils: A review, E O Aluyor , K O Obahiagbon , M Ori-Jesu . 2009.
 4 p. .
- [Burger et al. ()] 'Composition of the kernel oil and protein of the marula seed'. A E C Burger , J B M De Villiers
 , L M Du Plessis . South African Journal of Science 1987. 83 p. .
- [Knothe ()] 'Dependence of biodiesel fuel properties on the structure of fatty acid alkyl esters'. G Knothe . *Fuel Process Technology* 2005. 86 p. .
- [Moser et al. ()] 'Exhaust emissions and fuel properties of partially hydrogenated soybean oil methyl esters
 blended with ultra low sulfur diesel fuel'. B R Moser , A Williams , M J Haas , R L Mccormick . *Fuel Process Technology* 2009. 90 p. .
- [De Almeida et al. ()] 'Performance of a diesel generator fuelled with palm oil'. S C A De Almeida , C R Belchior , M V G Nascimento , L D S R Vieira , G Fleury . *Fuel* 2002. 81 (16) p. .
- [Masjuki et al. ()] 'Performance, emissions and wear characteristics of an I.D.I diesel engine using coconut
 blended oil'. H H Masjuki , M A Kalam , M A Maleque , A Kubo , T Nonaka . Journal of Automobile
 Engineering 2001. 3 p. .
- [Karmakar et al. ()] 'Properties of various plants and animals feedstocks for biodiesel production'. A Karmakar
 , S Karmakar , S Mukherjee . *Bioresource Technology* 2010. 101 (19) p. .
- [Misra and Murthy ()] 'Straight vegetable oils usage in a compression ignition engine -A review'. R D Misra , M
 S Murthy . Renewable and Sustainable Energy Reviews 2010. 14 (9) p. .