

Artificial Intelligence formulated this projection for compatibility purposes from the original article published at Global Journals. However, this technology is currently in beta. *Therefore, kindly ignore odd layouts, missed formulae, text, tables, or figures.*

Water Resources Assessment of the Manya Krobo District

G. K. Anornu¹, Dr. F. K.Y. Amevenku² and B. K. K ortatsi³

¹ Kwame Nkrumah University of Science and Technology (KNUST)

Received: 10 June 2012 Accepted: 1 July 2012 Published: 15 July 2012

6 Abstract

1

2

3

4

The study on water resources assessment carried out in the Upper Manya Krobo district of 7 the Eastern region, Ghana with the sole objective of identifying feasible options for water 8 supply augmentation to communities in the district. The methodology consisted of inventory 9 of boreholes and hand dug wells, rivers, streams, pipe schemes. Surveys conducted on the 10 hydrogeology, geomorphology and buildings (roof) to determine the prospect of constructing 11 underground dams and rain harvesting schemes. Interviews as well as sampling of 12 groundwater and laboratory measurements determined the quality status of groundwater. 13 Also carried out was limited pumping test. The results showed that groundwater potential is 14 generally low. Borehole yield varies from 0.48 m3h-1 to 12.00 m3h-1 with mean of 3.4 m3h-1 15 and standard deviation of 2.97 respectively. Generally, the southern half of the district seems 16 to have relatively higher yields than the northern half. Except for the high iron concentration, 17 which is mostly outside the WHO (2006) guideline values, other chemical constituents were 18 generally low and within the WHO (2004), guideline limits. The potential for rain harvesting 19 is high, however, in a few communities; sheds would need to be provided for the dual purposes 20 of school, community centre, etc on one hand and rain harvesting system on the other. The 21 geology and geomorphology of the district are suitable for underground dam construction, 22 however, more detailed hydrogeological investigations are required prior to construction. 23

24

25 Index terms—Ghana, Groundwater, Rain harvesting, underground dams, Upper Manya District.

²⁶ 1 Introduction

27 pper Manya Krobo district is one of the districts that benefited from the District Based Water and Sanitation

Component (DBWSC) of the Water and Sanitation Sector Programme Support (WSSPS) Phase II in the Eastern
 Region.

It has been implemented with Community Water and Sanitation Agency, Eastern Region Office, as the 30 facilitators. During the implementation of the programme in the districts, some challenges were observed to 31 32 be militating against the success of the programme. These included low success rate, low yield and poor water 33 quality. These challenges prevented the achievements of the expected targets of water delivery and coverage in the 34 district, which according to the Millennium Development Goals, should reach at least 75 % by 2015. Currently, about 52 % of communities have access to potable water supply in the whole of the Eastern Region. After much 35 cogitation and deliberation, it was realized that most of the water supply projects in the Eastern Region were 36 put in place without due reference to the source of supply and the amount of replenishment to the underlying 37 groundwater reservoirs leading to low yields, water shortages and deterioration water quality. As a first step to 38 address the challenges mentioned above, this research had the objective of water resource inventory and source 39

40 identification for water supply to communities in the Upper Manya Krobo district.

41 **2** II.

42 3 The Study Area

The Upper Manya Krobo district is located to the East of Ghana between latitude 6.17 o N and 6.55 o N and 43 longitude 0.10 o W and 0.33 o W. Figure 1 presents the location map of the study area. The geomorphology 44 consists of undulating topography with alternating series of ridges and valleys. The ridges attained elevations 45 between 350 m and 600 m, mostly separated by long narrow strike valleys in which small streams flow for most 46 parts of the year. The district falls under the Equatorial Climatic Zone. The climatic conditions of the area 47 are, characterized by high temperatures, ranging from 26 o C in August to about 32 o C in March. The area 48 has two rainfall regimes, with the first rainy season starting from May and ends in July with heaviest rainfall 49 occurring in June. The second rainy season starts from September and ends in October or early November. The 50 annual rainfall varies between 1200 mm and 1450 mm with a mean value of 1250 mm (Benneh and Dickson, 51 2004; ??ARM, 1998). Relative humidity is generally high throughout the year. 52

⁵³ 4 a) Size and distribution of population

The population of the district according to the 2000 population and housing census was 18,741. Out of this, 54 9,400 were females and 9,341 were males. With a growth rate of 2.5%, the estimated population of the district 55 stood as 25,205 as at the end of the year 2012. The major economic activity in the district is rain fed agriculture 56 using the slash and burn method. Also, petty trading and small-scale industry for dehydrating cassava dough 57 and extracting palm kernel oil form part of the economic activities in the district. Food crops like maize, cassava, 58 plantain and vegetables are cultivated throughout the district. Livestock farming is undertaken at the household 59 level. In communities along the Volta Lake, extensive fishing in the lake is their major occupation. As the effect 60 of these activities on water resources intensified with increases in human and livestock populations, settlements, 61 farming (using the "slash and burn" method and under shorter rotation periods), the use of agrochemicals, fishing 62 and charcoal production more land is being used in the district. 63

₆₄ 5 c) Geological Setting

The Voltaian Formation mainly underlies the Upper Manya Krobo district as a sedimentary basin that has more or less concentric distribution of sediments because of its overall gently synclinal form (Wright et al., 1985). The sediments of the Voltaian system range in age from Upper Proterozoic to Paleozoic and include facies interpreted as products of two ancient glaciations, one in the infra-cambrian and the other in the Upper Ordovician (Wright et al., 1985).

The rocks are commonly flat-bedded with a mean dip of about 5 o except at the eastern flank approximating 70 a tectonic contact with the Buem Formation ?? Mason, 1963). The Voltaian System has three main divisions, 71 72 which are the Lower, Middle and Upper Voltaian units (Junner and Hirst, 1946; ??rant, 1967; Annan Yorke and Cudjoe, 1971; ??ffaton et al., 1980). Nonetheless, the predominate rock that has underlain the Upper Manya 73 Krobo district is Upper Voltaian unit. The sediments, probably typify mosassic deposit that accompanied the 74 uplift in the Pan African event ?? Grant, 1967). The sediments consist primarily of sandstones and conglomerates 75 that contain pebbles of granite and other igneous rocks and quartzite fragments. The sandstones weather mainly 76 to sandy clay and fine sand in the numerous valleys. The Obosum and Oti Beds form only 2% of the total rock 77 cover of the Upper Manya district and occur as discontinuous unit along the bank of the Volta Lake (Fig. 2). 78

79 6 Materials And Methodology

The methodology considered was principally made of desk study, interviews, field measurement, laboratory analyses, map preparation and reporting.

The desk study involved re-evaluation of relevant literature notably hydrogeological and hydrological reports; 82 geological and topographic maps, drilling logs and borehole records. Borehole records and hydrogeological 83 information were collected from Water Research Institute (WRI), Community Water and Sanitation Agency 84 (CWSA), the Adventist Development and Relief Agency (ADRA). Hydro meteorological and hydrological data 85 were collected from Ghana Meteorological Services Agency (GMSA) and Hydrological Services Department (HSD) 86 of the Ministry of Water Resources, Works and Housing respectively. Hydrometeorological data (rainfall and 87 temperature) were obtained for two (2) meteorological stations (Anyaboni and Asesewa) in the study area. The 88 Upper Manya Krobo District Assembly provided data on the water resources and environmental plan for the 89 90 district. All the information gathered were collated, analysed and presented as the background of the study area. 91 Additionally, field data sheets were designed based on information gathered from the desk study to obtain further 92 primary data.

Field Reconnaissance survey was carried out in the entire district between September 8 th and 25 th , 2008 and 248 boreholes, 24 hand-dug wells and 41ephemeral streams were inventoried. Survey of roofs was also carried out in 42 communities in the district, which had low groundwater and surface water potentials to determine the suitability of the roofs for rain harvesting and the volume of rain water that each roof could harvest annually. Interviews were also conducted on a sample of the communities with regards to the adequacy of water supply, water quality problems, sanitation facilities etc. The field work also involved careful ground observations to delineate areas, which by their geological history and geomorphology could be suitable for underground dam
construction. Based on the results of the desk study and field reconnaissance survey, 13 boreholes were sampled
for water quality of which 2 of them were pump tested to ascertain their yields and analysis carried out using
Jacob Cooper methodology.

The boreholes sampled were randomly selected and distributed in such a way that they represented the whole 103 district. Sampling protocols described by Claasen (1982) and Barcelona et al. (1985) for chemical water quality 104 determination were strictly adhered to during the sample collection. Samples collected into 4:1 acidwashed 105 polypropylene containers after three-pore volumes purge. Each sample meant for trace metal determination 106 immediately filtered on site through 0.45 µm pore size on acetate cellulose filters. The filtrate transferred into 107 100 cm 3 polyethylene bottles and immediately acidified to pH < 2 by the addition of Merck TM ultra pure 108 nitric acid. Samples for anions analyses collected into 250 cm 3 polyethylene bottles without preservation. All 109 samples were stored in an icechest at a temperature of < 4 o C and transported to the Potable Water Quality 110 Laboratory of the Water Research Institute in Accra for analyses, which was carried out within three days. 111

Temperature, pH and electrical conductivity were measured 'in situ' using WTW-Multiline P4 Universal Meter. Chemical analyses of the samples were carried out using appropriate certified and acceptable international standard methods (APHA, 1998; Global Environmental Monitoring System/Water Operational Guide, 1988). An ionic balance was computed for each chemical sample and used as a basis for checking analytical results. In accordance with international standards, results with ionic balance error greater that 5% were rejected (Freeze & Cherry, 1997; Appelo & Postma, 1999).

118 IV.

¹¹⁹ 7 Results And Discussions a) Groundwater Resources Evalua-

120 tion

Data on 248 boreholes, 24 hand-dug wells in the district were collected and analysed, and results revealed complex 121 122 hydrogeological conditions. Much of the primary porosity of the bedrocks in the Upper Voltaian formation has 123 been destroyed due to consolidation and cementation (Kesse, 1985). The formation, therefore, have very little 124 intergranular porespace and are thus characterized by insignificant primary porosity and permeability. The 125 rocks however, are fractured and weathered as they occur close to the surface. Cavities along joints, bedding and cleavage planes frequently act as channels for groundwater transmission and storage. Where these fissures 126 are prevalent, incessant, interconnected and/or filled with permeable material, percolation and circulation of 127 significant quantity of water do occur. 128

The pumping test analysis indicated that the trend lines of most of the field data cut below the zero on 129 the residual drawdown axes (Fig. 3) suggesting that the aquifers are generally discrete and limited in extent. 130 Depth to water varied throughout the district but was generally shallow, ranging from 0.5 m to 18.3 m with 131 mean and median values of 6.4 m and 4.2 m respectively. The depth of boreholes varied from 22 m to 84 m 132 with mean and median values of 35 m and 25 m respectively. Data on potentiometric heads indicate that the 133 potentiometric surface resembles that of the land surface elevation. Groundwater generally occurs under semi-134 confined conditions, but confined conditions also exist at a few places. Static water levels (SWL) ranged from 135 $1.0~\mathrm{m}$ to $20~\mathrm{m}$ below the land surface. Transmissivities values were between 0.3 and 70.0 m 2 d --1 . This range 136 is consistent with transmissivity values obtained in similar geological formation in the Afram Plains (Buckley, 137 1986; Minor et al., 1995). Estimated well yields range from 0.25 to 12.00 m 3 h -1 with mean 3.2 m 3 h -1 and 138 standard deviation 3.5 respectively. The median yield is 1.6. m 3 h -1. The histogram in Fig. 4 shows that 139 the yields of the boreholes were discontinuous and not normally distributed. In such situations, non-parametric 140 statistics needs to be applied (UNESCO/WHO/UNEP, 1996; Caritat, 1998). Therefore, the use of the median 141 is more robust than the mean in describing the central tendency of the yield distribution (Caritat, 1998). The 142 low median value, suggests that generally the yields of majority of boreholes in the Upper Manya Krobo district 143 are low. Nonetheless, boreholes are apparently higher yielding and more numerous in the areas underlain by the 144 Upper Voltaian than those of the Obosum and Oti beds areas. Spatially, relatively higher yields were obtained in 145 the southern half of the district than in the northern half. 1 & 2). The groundwater was slightly acidic with pH 146 in the range 5.5-7.0 pH units with median 6.3 pH units (Tables 1 & 2) as compared to natural water pH range 147 of 4.5-9.0 pH units (Langmuir, 1995). EC levels varied from 76 µS cm -1 to 1198 µS cm -1, with median 240 µS 148 cm -1. Groundwater in the district was relatively turbid with turbidity values ranging from 0.2 to 68 NTU and 149 a mean value of 13 NTU. The alkalinity of the groundwater values varied largely ranging from 6.0 mgl -1 to 432 150 mgl -1, with a mean value of 114.6 mgl -1. 151

152 8 RESIDUAL DRAWDOWN GRAPH

¹⁵³ 9 c) Hydrochemical facies

The chemical trend of groundwater in the Upper Manya Krobo district was derived using the Piper trilinear diagrams (Piper, 1944). Four main water types (labelled A-D) characterized the district. In the first type (A), alkaline earth and weak acids, dominate the chemical properties of the groundwater, that is the groundwater consists mainly of low salinity calcium bicarbonate (Ca (HCO 3) 2). This water type designated (A) occurs

principally at Agbetsom, Akatawiah, Akusu Saisa, Dawatrim, Kwabia Asaasehene and New Anyaboni Quarters. 158 The second type (B and D) consists of mixed water type where no particular ion pair exceeds 50 %. This 159 water type is found mainly at Takorase and Abrese Akwenor. Alkali and strong acids dominate the chemical 160 properties of the third water type (C) that is, this water type has Na as the main cation and Cl or SO 4 as the 161 principal anion and mainly found at Seseame Sisi, Agome Bisa, Brepon Kpeti and Kabu. In the fourth water 162 type (E), non-carbonate hardness (permanent hardness) exceeds 50%. In other words, Mg 2+ Groundwater has 163 good quality for domestic use if it is soft, low in total dissolved solids (TDS) and free from poisonous chemical 164 constituents as well as bacteria ??Karanth, 1994; ??ortatsi et al., 2008). The quality of groundwater in the Upper 165 Manya district evaluated in terms of physico-chemical and bacteriological parameters would ascertain whether 166 the water is soft, low in TDS, free from deleterious chemical constituents and bacteria. 167

Water is considered soft if the total hardness is between 0 -75 mg l -1 of CaCO 3; moderately hard if the 168 total hardness is between 75-150 mg l \cdot 1 of CaCO 3 , hard if the total hardness is between 150-300 mg l \cdot 1 of 169 CaCO 3 and very hard if the total hardness is greater than 300 mg l -1 of CaCO 3. Total hardness values of 170 the groundwater ranged from 16 mg l -1 to 560 mg l -1 of CaCO 3 with a median value of 143 mg l -1 of CaCO 171 3 suggesting that about half the boreholes are soft to moderately hard. The TDS of the groundwater is in the 172 range 41-659 mg l -1 with a median 132 mg l -1 while the WHO (2004) recommended upper limit for drinking 173 174 water is 1000 mg l -1. This implies that the water quality is good with respect to TDS. Similarly, all the major 175 ions (calcium, magnesium, sodium, bicarbonate, sulphate, and chloride) are within the WHO (2004) limits for drinking water. Nitrate (NO 3 -N) levels are generally low with values in the range 0.74-8.89 mg l -1 and median 176 1.37 mg l -1 and, therefore, within the WHO guideline value of 10 mg l -1 (Table 2). Iron concentration in the 177 groundwater in the district is relatively high. It is in the range 0.01-5.23 mg l -1 with a median 0.36 mg l -1. 178 The ??HO (2004) guideline value is 0.3 mg l -1, suggesting that the majority of the well in the Manya Krobo 179 district have iron problem. On the contrary, manganese (Mn 2+) concentration in the groundwater is generally 180 low. Its range was 0.02 -0.64 mg l -1, with a median value of 0.33 mg l -1 as against the WHO (2004) provisional 181 upper limit of 0.5 mg l -1 signifying that a larger proportion of the boreholes are potable with regards to Mn 2+ 182 183

The presence of high Fe 2+ and Mn 2+ concentrations in water do not particularly pose physiological problems. 184 However, they have the ability of producing aesthetic or sensory effect due to discoloring of water, i.e. high 185 Fe 2+ concentrations results in reddish brown coloration, while high Mn 2+ concentrations results in black 186 coloration. These sensory effects can lead to the total rejection of the boreholes. It also results in staining of 187 laundry and sanitary wares (WHO, 2004). Very distinct reddish brown coloration in water pertained in some 188 abandoned boreholes in some communities during sampling period. The reddish colouration might probably have 189 led to the abandonment of the boreholes. Other trace metals measured only have background concentrations. 190 Bacteriological survey of boreholes in the Upper Manya district suggests that the boreholes are generally free 191 from E. coli and total coli form but some hand-dug wells contain bacteria due to unhygienic conditions around 192 the hand-dug wells (CSIR-WRI, 2009). 193

¹⁹⁴ 10 e) Rainwater Harvesting

Generally, rainwater harvesting requires simple arrangement to collect, store, treat and to distribute the captured rainwater. Rainwater offers additional advantages in water quality for domestic use. It is naturally soft (unlike well water), contains almost no dissolved minerals or salts, is free of chemical treatment, and is a relatively reliable source of water for households. Rainwater collected and used on site can supplement or replace other sources of household water. Rainwater can be drunk if properly stored and suitably treated.

²⁰⁰ 11 f) Availability of rain for collection (harvesting)

The annual rainfall in the area is in the ranges 120-160 cm with a mean of about 130cm and median 125 cm (Dickson and Benneh, 2004) present the mean annual rainfall distributions for the respective stations. The data covered a period 1939-1996. The rainfall pattern is bimodal, with the major peak in June and minor peak in October. In August, there is a minor dry spell. the projected population that the rain harvested system can serve.

206

? Mean annual rainfall of 1.2 m; ? Rainfall available for harvesting is only 70 per cent of the mean annual
 precipitation since there are partial losses due to interception, evaporation etc.

- 209 ? Daily per capita consumption of 25 litres;
- 210 ? Duration of usage of 366 days;
- 211 ? Average household size of 5 persons.

Using the criteria above the volume of rainwater likely to be harvested annually from metallic roofs, the average number of persons to be served by the expected harvested volume of water and the estimated average current population coverage of settlement within the various area councils have been computed and presented in Table 3. The results indicate that the estimated annual harvested rainwater from approximately 43 major settlements within the Upper Manya district varies from 807.77 to 10,143.00 m 3. The results also suggest that 76.8 % or thirty three (33) of the settlements could harvest water to suffice the inhabitants with water for their daily needs annually. The remaining twelve (12) communities or 23.2 % had few metallic roofed buildings. In these poor communities, funds used for the search for groundwater and the drilling of unproductive boreholes can be channelled into the provision of sheds or pavilions, which can be utilised dually as community centres, schools etc. on one hand and rain harvesting system on the other hand. With such basic infrastructure provision, enough volume of water can be obtained to provide for the needs of these settlements. Another solution would be to utilise raw water from the Volta Lake for their requirements.

Problems that may militate against rain harvesting in the Upper Manya Krobo district.

Most buildings in Upper Manya Krobo district were unsuitable for rainwater harvesting. Structural modification of buildings particularly attaching a gutter system will be necessary to make them suitable for rainwater harvesting. The cost of such modification will be beyond the financial means of most families living in the district. Additionally, some villagers living in houses roofed with straws would probably not have the means and resources to adopt such rainwater harvesting technique.

The next problem is how to store rainwater for dry season. Currently, in the communities visited, storing 230 rainwater in vessels for later use will be practically impossible, for it will require a large number of containers. 231 Various techniques of water storage are available but the most feasible option is to build large underground 232 concrete tanks. Again, investment cost for storage system can be prohibitive for most households in the district. 233 234 Pollution may also be a major problem in spite of the fact that rainwater in rural areas as the Upper Manya 235 district remote from atmospheric and industrial pollution is practically clean except for some dissolved gases it 236 may pick up while it precipitates through the atmosphere. Rainwater often contains dissolvable atmospheric gases proportionate to their abundance. It also contains sediments, dust, bird droppings, aerosols, particulates, 237 and anthropogenic gases that may result from biomass and fossil fuel burning. These are often the main sources 238 of rainwater pollution. Since rainwater is not pure water, some precautions have to be observed before the water 239 is consumed. Sediments removal and further water purification could be carried out by using slow sand filtration 240 system with activated charcoal. Slow sand filter is low energy consuming process that has great adaptability 241 in components and application; also, its maintenance requirement is minimal. The availability of numerous 242 ephemeral springs and streams as well as the favourable geomorphology and geology satisfy the criteria for sand 243 storage dam construction in the Upper Manya Krobo district. Therefore, in addition to rain harvesting system 244 recommended for the Upper Manya district, construction of sand storage dam is also a feasible option for the 245 district. However, there is the need to conduct more detailed hydrogeological and bacteriological investigations 246 to determine the conditions that exist underground, the type of microbes that may be available in the stored 247 248 water, nutrient levels and the types of microbes that exist underground to purify the water. V. 249

250 12 Conclusions

The option for water supply augmentation include the provision of additional boreholes, rain harvesting and sand storage (underground) dam construction. In spite of the fact that, groundwater potential is generally low in the Upper Manya district, intensive groundwater exploration in some localities particularly in the southern half of the district where boreholes are relatively higher yielding than the north should result in adequate yield for existing water supply augmentation. Generally, the quality of groundwater encountered is physiologically safe for drinking purposes. The only perennial yielding spring (Ternguanya), could be protected for supply of water to nearby settlements.

The potential exists for harvesting clean rain water in substantial quantities to supplement water supply from current sources. However, existing metallic roofs need modification for rain harvesting. In communities with thatch buildings, rain harvesting schemes can be effective when installed on institutional and church buildings in the rural communities. Individual household schemes with ferro-cement tanks may also be considered for rural communities with no other option for water supply. This is because the size of storage system required for using harvested rainfall to meet the full demand of an average rural community may be too prohibitive and not cost-effective.

Detailed designs, especially of receptacles and storage facilities are required to plan for an effective programme to pursue this option; while educational programmes to reawaken the populace on the importance and benefits of harvesting rain water at the local level; is required.

The geology and geomorphology of this district are apparently suitable for under ground dam construction. However, more detailed hydrogeological investigations are required prior to construction.

¹(E) \odot 2012 Global Journals Inc. (US)



Figure 1: UFig. 1 :



Figure 2: Fig. 2 :



Figure 3: Fig. 3:



Figure 4: Fig. 4 :



Figure 5:

1

(E)



 $\mathbf{2}$

Figure 7: Table 2 :

	Average number of persons expected to	Average estimate of current
Area Council	be served by estimated harvested	population of the settle- ment
	volume of water.	
Anyaboni Bisa	464.26	379.75
Mensah Dawa	332.00	142.55
Sekesua	384.25	286.30
Konkoney Sisiamang	452.45	208.25
Ternguanya	655.20	357.70
Asesewa	204.11	284.20

Figure 8: Table 3 :

12 CONCLUSIONS

- 270 [Stumn and Morgan ()], W Stumn, J J Morgan. 1981. New York: Aquatic Chemistry. Willey. p. 780.
- [Piper ()] 'A graphic procedure in the Geochemical interpretation of water analyses'. A M Piper . Am. Geophysical
 Union, Trans 1944. 25 p. .
- [Dickson and Benneh ()] A New Geography of Ghana fifth edition, K B Dickson , G Benneh . 2004. London.
 Longmans Group Limited
- [Onder and Yilmar ()] 'A tool of sustainable development and management of Groundwater resources'. H Onder
 , M Yilmar . European Water 2005. 2005. 11 p. .
- [Santos and Frangipani ()] 'Barragens Submersas -Uma Alternativa para o Nordeste Brasileira'. Dos Santos , J-P
 A Frangipani . Congreso Brasileiro de Geología de Engenharia, (São Paulo) 1978. 2 p. .
- [Appelo and Postma ()] Chemical analysis of groundwater. Geochemistry, groundwater and pollution, C A Appelo
 , D Postma . 1999. Balkema Rotterdam/Brookfield.
- [Wright et al. ()] Geology and mineral resources of West Africa, J B Wright , D A Hastings , W Jones , H
 Williams , R . 1985. London: George Allen and Unwin Publishers. p. 187.
- [Yorke and Cudjoe ()] Geology of the Voltaian Basin (summary of current ideas) Special bulletin of oil exploration.
 Ghana Geological Survey department, Annan Yorke, R Cudjoe, JE. 1971. p. 29.
- [Caritat et al. ()] 'Groundwater composition near the nickel-copper smelting industry on the Kola Peninsula,
 central Barents Region (NW Russia and NE Norway)'. D P Caritat, S Danilova, Ø J?ger, C Reimann, G
 Storrø. Journal of Hydrology 1998. 208 p. .
- [Claasen ()] Guidelines and techniques for obtaining water sample that accurately represent the quality of an aquifer, H C Claasen . 82-1024. 49pp. 1982. (U.S. Geological Survey Open File Report)
- [Guidelines for Drinking Water Quality-Health Criteria and other Supporting Information World Health Organization ()]
 'Guidelines for Drinking Water Quality-Health Criteria and other Supporting Information'. World Health
 Organization 1984. (World Health Organization)
- 293 [Guidelines for Drinking Water Quality. World Health Organization, /Genava World Health Organization ()]
- 'Guidelines for Drinking Water Quality. World Health Organization, /Genava'. World Health Organization
 2004.
- [Ishida et al. ()] Satoshi Ishida , Motoi Kotoku , Eiichi Abe , FazalM A , Takeo Tsuchihara , Masayuki Maizumi
 Construction of subsurface dams and their impact on the environment, 2003. 50 p. .
- [Barcelona et al. ()] 'Practical guide for groundwater sampling'. M Barcelona, J P Gibb, J Helfrich, E E Garske
 . Ilinois State Water Survey ISWS Contract Report 1985. 37.
- [Standard methods for the Examination of Water and Wastewater (20 th edn ()] Standard methods for the Examination of Water and Wastewater (20 th edn, 1998. Washington DC: APHA.
- Junner and Hirst ()] 'The Geology and hydrology of the Voltaian Basin'. N Junner , T Hirst . Gold Coast
 Geological Survey 1946. 50 (8) p. p.
- [Grant ()] 'The Late precambrian to early Palaezoic Pan African Orogeny in Ghana'. N K Grant . Geological
 Society of America Bulletin 1969. 80 p. .
- 306 [Kesse ()] The mineral and rock resources of Ghana, G O Kesse . 1985. Rotterdam, A.A. Balkema.